

UTILITY APPLICATION

UNDER 37 CFR § 1.53(B)


TITLE: SUBCUTANEOUS ELECTRODE WITH IMPROVED  
CONTACT SHAPE FOR TRANSTHORACIC  
CONDUCTION

APPLICANT(S): GUST H. BARDY, M.D.; RICCARDO CAPPATO,  
M.D.; WILLIAM J. RISSMANN; GARY H.  
SANDERS

Correspondence Enclosed:

Utility Application Transmittal Sheet and FY 2001  
Fee Transmittal Sheet (2 pgs); Specification  
(176 pgs); Claims (43 pgs); Drawings (72 pgs);  
Abstract (1 pg); and Return Postcard

"EXPRESS MAIL" Mailing Label Number EL573394965US Date of Deposit August 27, 2001 I  
hereby certify under 37 CFR §1.10 that this correspondence is being deposited with the United  
States Postal Service as "Express Mail Post Office to Addressee" with sufficient postage on the  
date indicated above and is addressed to the Commissioner for Patents, Washington, D.C. 20231.



SUBCUTANEOUS ELECTRODE WITH IMPROVED CONTACT SHAPE FOR  
TRANSTHORACIC CONDUCTION

Inventors:

Gust H. Bardy

Riccardo Cappato

William J. Rissmann

Gary H. Sanders

032580.0022.UTL

FIELD OF THE INVENTION

The present invention relates to an apparatus and method for performing electrical cardioversion/defibrillation and optional pacing of the heart via a totally subcutaneous non-transvenous system.

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a continuation-in-part of U.S. patent application entitled "SUBCUTANEOUS ONLY IMPLANTABLE CARDIOVERTER-DEFIBRILLATOR AND OPTIONAL PACER," having Serial No. 09/663,606, filed September 18, 2000, pending, and U.S. patent application entitled "UNITARY SUBCUTANEOUS ONLY IMPLANTABLE CARDIOVERTER-DEFIBRILLATOR AND OPTIONAL PACER," having Serial No. 09/663,607, filed September 18, 2000, pending, of which both applications are assigned to the assignee of the present application, and the disclosures of both applications are hereby incorporated by reference.

In addition, the present application is filed concurrently herewith U.S. patent application entitled "DUCKBILL-SHAPED IMPLANTABLE CARDIOVERTER-DEFIBRILLATOR AND METHOD OF USE," U.S. patent application entitled "CERAMICS AND/OR OTHER MATERIAL INSULATED SHELL FOR ACTIVE AND NON-ACTIVE S-ICD CAN," U.S. patent application entitled "SUBCUTANEOUS ELECTRODE FOR

TRANSTHORACIC CONDUCTION WITH IMPROVED INSTALLATION  
CHARACTERISTICS," U.S. patent application entitled "SUBCUTANEOUS  
ELECTRODE FOR TRANSTHORACIC CONDUCTION WITH HIGHLY MANEUVERABLE  
INSERTION TOOL," U.S. patent application entitled "SUBCUTANEOUS  
5 ELECTRODE FOR TRANSTHORACIC CONDUCTION WITH LOW-PROFILE  
INSTALLATION APPENDAGE AND METHOD OF DOING SAME," U.S. patent  
application entitled "SUBCUTANEOUS ELECTRODE FOR TRANSTHORACIC  
CONDUCTION WITH INSERTION TOOL," U.S. patent application  
entitled "METHOD OF INSERTION AND IMPLANTATION FOR IMPLANTABLE  
10 CARDIOVERTER-DEFIBRILLATOR CANISTERS," U.S. patent application  
entitled "CANISTER DESIGNS FOR IMPLANTABLE CARDIOVERTER-  
DEFIBRILLATORS," U.S. patent application entitled "RADIANT CURVED  
IMPLANTABLE CARDIOVERTER-DEFIBRILLATOR CANISTER," U.S. patent  
application entitled "CARDIOVERTER-DEFIBRILLATOR HAVING A  
FOCUSED SHOCKING AREA AND ORIENTATION THEREOF," U.S. patent  
application entitled "BIPHASIC WAVEFORM FOR ANTI-BRADYCARDIA  
PACING FOR A SUBCUTANEOUS IMPLANTABLE CARDIOVERTER-  
DEFIBRILLATOR," U.S. patent application entitled "BIPHASIC  
WAVEFORM FOR ANTI-TACHYCARDIA PACING FOR A SUBCUTANEOUS  
20 IMPLANTABLE CARDIOVERTER-DEFIBRILLATOR," and U.S. patent  
application entitled "POWER SUPPLY FOR A SUBCUTANEOUS  
IMPLANTABLE CARDIOVERTER-DEFIBRILLATOR," the disclosures of  
which applications are hereby incorporated by reference.

BACKGROUND OF THE INVENTION

Defibrillation/cardioversion is a technique employed to counter arrhythmic heart conditions including some tachycardias in the atria and/or ventricles. Typically, electrodes are employed to stimulate the heart with electrical impulses or shocks, of a magnitude substantially greater than pulses used in cardiac pacing.

Defibrillation/cardioversion systems include body implantable electrodes and are referred to as implantable cardioverter/defibrillators (ICDs). Such electrodes can be in the form of patches applied directly to epicardial tissue, or at the distal end regions of intravascular catheters, inserted into a selected cardiac chamber. U.S. Pat. Nos. 4,603,705, 4,693,253, 4,944,300, 5,105,810, the disclosures of which are all incorporated herein by reference, disclose intravascular or transvenous electrodes, employed either alone or in combination with an epicardial patch electrode. Compliant epicardial defibrillator electrodes are disclosed in U.S. Pat. Nos. 4,567,900 and 5,618,287, the disclosures of which are incorporated herein by reference. A sensing epicardial electrode configuration is disclosed in U.S. Pat No. 5,476,503, the disclosure of which is incorporated herein by reference.

10 541614-036501  
In addition to epicardial and transvenous electrodes, subcutaneous electrode systems have also been developed. For example, U.S. Patent Nos. 5,342,407 and 5,603,732, the disclosures of which are incorporated herein by reference, teach the use of a pulse monitor/generator surgically implanted into the abdomen and subcutaneous electrodes implanted in the thorax. This system is far more complicated to use than current ICD systems using transvenous lead systems together with an active can electrode and therefore it has o practical use. It has in fact never been used because of the surgical difficulty of applying such a device (3 incisions), the impractical abdominal location of the generator and the electrically poor sensing and defibrillation aspects of such a system.

Recent efforts to improve the efficiency of ICDs have led manufacturers to produce ICDs which are small enough to be implanted in the pectoral region. In addition, advances in circuit design have enabled the housing of the ICD to form a subcutaneous electrode. Some examples of ICDs in which the housing of the ICD serves as an optional additional electrode are described in U.S. Pat. Nos. 5,133,353, 5,261,400, 5,620,477, and 5,658,321 the disclosures of which are incorporated herein by reference.

ICDs are now an established therapy for the management of life threatening cardiac rhythm disorders, primarily ventricular

fibrillation (V-Fib). ICDs are very effective at treating V-Fib, but are therapies that still require significant surgery.

As ICD therapy becomes more prophylactic in nature and used in progressively less ill individuals, especially children at risk of cardiac arrest, the requirement of ICD therapy to use intravenous catheters and transvenous leads is an impediment to very long term management as most individuals will begin to develop complications related to lead system malfunction sometime in the 5-10 year time frame, often earlier. In addition, chronic transvenous lead systems, their reimplantation and removals, can damage major cardiovascular venous systems and the tricuspid valve, as well as result in life threatening perforations of the great vessels and heart. Consequently, use of transvenous lead systems, despite their many advantages, are not without their chronic patient management limitations in those with life expectancies of >5 years. The problem of lead complications is even greater in children where body growth can substantially alter transvenous lead function and lead to additional cardiovascular problems and revisions. Moreover, transvenous ICD systems also increase cost and require specialized interventional rooms and equipment as well as special skill for insertion. These systems are typically implanted by cardiac electrophysiologists who have had a great deal of extra training.

In addition to the background related to ICD therapy, the present invention requires a brief understanding of automatic external defibrillator (AED) therapy. AEDs employ the use of cutaneous patch electrodes to effect defibrillation under the direction of a bystander user who treats the patient suffering from V-Fib. AEDs can be as effective as an ICD if applied to the victim promptly within 2 to 3 minutes.

AED therapy has great appeal as a tool for diminishing the risk of death in public venues such as in air flight. However, an AED must be used by another individual, not the person suffering from the potential fatal rhythm. It is more of a public health tool than a patient-specific tool like an ICD. Because >75% of cardiac arrests occur in the home, and over half occur in the bedroom, patients at risk of cardiac arrest are often alone or asleep and can not be helped in time with an AED. Moreover, its success depends to a reasonable degree on an acceptable level of skill and calm by the bystander user.

What is needed therefore, especially for children and for prophylactic long term use, is a combination of the two forms of therapy which would provide prompt and near-certain defibrillation, like an ICD, but without the long-term adverse sequelae of a transvenous lead system while simultaneously using most of the simpler and lower cost technology of an AED. What is also needed is a cardioverter/defibrillator that is of simple



design and can be comfortably implanted in a patient for many years.

#### SUMMARY OF THE INVENTION

5

One embodiment of the present invention provides a lead electrode assembly for use with an implantable cardioverter-defibrillator subcutaneously implanted outside the ribcage between the third and eighth ribs comprising an electrode.

#### BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of the invention, reference is now made to the drawings where like numerals represent similar objects throughout the figures where:

FIG. 1 is a schematic view of a Subcutaneous ICD (S-ICD) of the present invention;

FIG. 2 is a schematic view of an alternate embodiment of a subcutaneous electrode of the present invention;

FIG. 3 is a schematic view of an alternate embodiment of a subcutaneous electrode of the present invention;

FIG. 4 is a schematic view of the S-ICD and lead of FIG. 1 subcutaneously implanted in the thorax of a patient;

FIG. 5 is a schematic view of the S-ICD and lead of FIG. 2 subcutaneously implanted in an alternate location within the thorax of a patient;

FIG. 6 is a schematic view of the S-ICD and lead of FIG. 3 subcutaneously implanted in the thorax of a patient;

FIG. 7 is a schematic view of the method of making a subcutaneous path from the preferred incision and housing implantation point to a termination point for locating a subcutaneous electrode of the present invention;

FIG. 8 is a schematic view of an introducer set for performing the method of lead insertion of any of the described embodiments;

FIG. 9 is a schematic view of an alternative S-ICD of the present invention illustrating a lead subcutaneously and serpigiously implanted in the thorax of a patient for use particularly in children;

FIG. 10 is a schematic view of an alternate embodiment of an S-ICD of the present invention;

FIG. 11 is a schematic view of the S-ICD of FIG. 10 subcutaneously implanted in the thorax of a patient;

FIG. 12 is a schematic view of yet a further embodiment where the canister of the S-ICD of the present invention is shaped to be particularly useful in placing subcutaneously adjacent and parallel to a rib of a patient; and

FIG. 13 is a schematic of a different embodiment where the canister of the S-ICD of the present invention is shaped to be particularly useful in placing subcutaneously adjacent and parallel to a rib of a patient.

5 FIG. 14 is a schematic view of a Unitary Subcutaneous ICD (US-ICD) of the present invention;

FIG. 15 is a schematic view of the US-ICD subcutaneously implanted in the thorax of a patient;

FIG. 16 is a schematic view of the method of making a subcutaneous path from the preferred incision for implanting the US-ICD.

FIG. 17 is a schematic view of an introducer for performing the method of US-ICD implantation; and

FIG. 18 is an exploded schematic view of an alternate embodiment of the present invention with a plug-in portion that contains operational circuitry and means for generating cardioversion/defibrillation shock waves.

FIG. 14(a) is a side plan view of an embodiment of a lead electrode assembly with a top-mounted fin;

20 FIG. 14(b) is a top plan view of an embodiment of a lead electrode assembly with a top-mounted fin;

FIG. 14(c) is a side plan view of a section of the lead in an embodiment of the lead electrode assembly;

FIG. 14(d) is a cross-sectional view of a filar in the lead in an embodiment of the lead electrode assembly;

FIG. 14(e) is a cross-sectional view of the lead fastener of an embodiment of a lead electrode assembly;

5 FIG. 14(f) is an exploded view of the lead fastener of an embodiment of a lead electrode assembly;

FIG. 15(a) is a cross-sectional front plan view of an embodiment of a lead electrode assembly with a top-mounted fin;

10 FIG. 15(b) is a top plan view of an embodiment of a lead electrode assembly with a top-mounted fin;

FIG. 16(a) is a perspective view of an embodiment of a lead electrode assembly with a top-mounted fin;

FIG. 17(a) is a cross-sectional side plan view of an embodiment of a lead electrode assembly with a top-mounted fin and a molded cover;

FIG. 17(b) is a cross-sectional side plan view of an embodiment of a lead electrode assembly with a top-mounted fin that is slope-shaped and a molded cover;

20 FIG. 17(c) is cross-sectional front plan view of an embodiment of a lead electrode assembly with a top-mounted fin and a molded cover;

FIG. 17(d) is an exploded top plan view of the lead fastener in an embodiment of a lead electrode assembly with a top-mounted fin and a molded cover;

FIG. 17(e) is a bottom plan view of an embodiment of a lead electrode assembly with a top-mounted fin and a molded cover;

FIG. 17(f) is a side plan view of an embodiment of a lead electrode assembly with a top-mounted fin and a molded cover;

5 FIG. 17(g) is a top plan view of an embodiment of a lead electrode assembly with a top-mounted fin and a molded cover;

FIG. 18(a) is a side plan view of an embodiment of a lead electrode assembly with an elongated top-mounted fin and a molded cover;

10 FIG. 18(b) is a top plan view of an embodiment of a lead electrode assembly with an elongated top-mounted fin and a molded cover;

FIG. 18(c) is a bottom plan view of an embodiment of a lead electrode assembly with an elongated top-mounted fin and a molded cover;

15 FIG. 19 is a side plan view of a lead electrode assembly demonstrating the curvature of the electrode;

20 FIG. 20(a) is a top plan view of the backing layer and electrode of an embodiment of a lead electrode assembly with a side-mounted fin;

FIG. 20(b) is a side plan view of the backing layer and electrode of an embodiment of a lead electrode assembly with a side-mounted fin;

FIG. 20(c) is a bottom plan view of an embodiment of a lead electrode assembly with a side-mounted fin;

FIG. 20(d) is a bottom plan view of an embodiment of a lead electrode assembly with a side-mounted fin with a slope-shape;

5       FIG. 21(a) is a side plan view of a lead electrode assembly with a top-mounted loop;

FIG. 21(b) is a cross-sectional rear plan view of a lead electrode assembly with a top-mounted loop;

10       FIG. 21(c) is a top plan view of a lead electrode assembly with a top-mounted loop;

15       FIG. 22(a) is a top plan view of a backing layer for use in an embodiment of a lead electrode assembly with a top-mounted fin formed as part of the backing layer;

20       FIG. 22(b) is a top plan view of an embodiment of a lead electrode assembly with a top-mounted fin formed as part of the backing layer;

FIG. 22(c) is a side plan view of an embodiment of a lead electrode assembly with a top-mounted fin formed as part of the backing layer;

25       FIG. 22(d) is a front plan view of an embodiment of a lead electrode assembly with a top-mounted fin formed as part of a backing layer;

FIG. 22(e) is a side plan view of an embodiment of a lead electrode assembly with a top-mounted fin formed as part of a two-piece backing layer;

FIG. 22(f) is a front plan view of an embodiment of a lead electrode assembly with a top-mounted fin formed as part of a two-piece backing layer;

FIG. 23(a) is a front plan view of the embodiment of the lead electrode assembly of FIG. 22(e) and (f) in an upright position;

FIG. 23(b) is a front plan view of the embodiment of the lead electrode assembly of FIG. 22(e) and (f) illustrating the ability of the fin to fold;

FIG. 24(a) is a front plan view of an embodiment of a lead electrode assembly with a top-mounted tube formed as part of a backing layer;

FIG. 24(b) is a side plan view of an embodiment of a lead electrode assembly with a top-mounted tube formed as part of a backing layer;

FIG. 24(c) is a top plan view of an embodiment of a lead electrode assembly with a top-mounted tube formed as part of a backing layer;

FIG. 25(a) is a front plan view of an embodiment of a lead electrode assembly with a top-mounted fin connected with flexible joining material in an upright position;

FIG. 25(b) is a front plan view of an embodiment of a lead electrode assembly with a top-mounted fin connected with flexible joining material in a folded position;

FIG. 25(c) is a top plan view of an embodiment of a lead electrode assembly with a top-mounted fin connected with flexible joining material in an upright position;

FIG. 26 is a perspective view of an embodiment of a lead electrode assembly in which the appendage is a cylindrical tube;

FIG. 27 is a perspective view of an embodiment of a lead electrode assembly in which the appendage is a tube with a substantially triangular cross section;

FIGS. 28(a)-(d) are top plan views of embodiments of lead electrode assemblies illustrating shapes of the electrode and the lines of the lead;

FIGS. 28(e)-(h) are bottom plan views of embodiments of lead electrode assemblies illustrating shapes of the electrode;

FIG. 29 is a perspective view of a custom hemostat for lead electrode assembly implantation;

FIG. 30(a) is a perspective view of a patient's ribcage showing the orientation of the components in an implanted S-ICD system;

FIG. 30(b) is a cross-sectional side plan view of a patient's rib cage, skin, fat and the lead of the lead electrode assembly;



FIG. 31 is a front plan view illustrating the incision point for the surgery to implant the lead electrode assembly;

FIG. 32(a) is a cross-sectional bottom plan view of a patient along line 32(a) of FIG. 31 illustrating the creation of a subcutaneous path for implantation of the lead electrode assembly of an S-ICD system;

FIG. 32(b) is a perspective view of a lead electrode assembly captured by a custom hemostat;

FIG. 32(c) is a cross-sectional bottom plan view of a patient along line 32(a) of FIG. 31 illustrating the implantation of a lead electrode assembly via the subcutaneous path;

FIG. 32(d) is a top view of a lead electrode assembly captured by a custom hemostat;

FIG. 33(a) is a perspective view of a rail of an embodiment of the lead electrode assembly;

FIG. 33(b) is a cross-sectional front plan view of an embodiment of the lead electrode assembly where the appendage is a rail;

FIG. 33(c) is a top plan view of an embodiment of the lead electrode assembly where the appendage is a rail;

FIG. 34 is a top view of an embodiment of the lead electrode assembly where the appendage is a rail;

FIG. 35(a) is a perspective view of a lead electrode assembly manipulation tool with a rail fork;

FIG. 35(b) is a top plan view of a lead electrode assembly manipulation tool with a rail fork;

5 FIG. 35(c) is a side plan view of a lead electrode assembly manipulation tool with a rail fork;

FIG. 35(d) is a top plan view of a lead electrode assembly having a rail captured by a lead electrode assembly manipulation tool with a rail fork;

FIG. 36(a) is a cross-sectional side plan view of a lead electrode assembly with a pocket;

FIG. 36(b) is a top plan view of a lead electrode assembly with a pocket;

FIG. 36(c) is a cross-sectional side plan view of a lead electrode assembly with a pocket and a fin;

FIG. 37(a) is a bottom plan view of a lead electrode assembly with a pocket;

FIG. 37(b) is a top plan view of a lead electrode assembly with a pocket;

20 FIG. 38(a) is a top plan view of a lead electrode assembly manipulation tool with a paddle;

FIG. 38(b) is a side plan view of a lead electrode assembly manipulation tool with a paddle;

FIG. 38(c) is a top plan view of a lead electrode assembly with a pocket captured by a lead electrode assembly manipulation tool with a paddle;

FIG. 39(a) is a cross-sectional rear plan view of a lead electrode assembly with a first channel guide and a second channel guide;

FIG. 39(b) is a top plan view of a lead electrode assembly with a first channel guide and a second channel guide;

FIG. 40(a) is a top plan view of a lead electrode assembly manipulation tool with a channel guide fork;

FIG. 40(b) is a top plan view of a lead electrode assembly with a first channel guide and a second channel guide captured by a lead electrode assembly manipulation tool with a channel guide fork;

FIG. 41(a) is a perspective view of a subcutaneous implantable cardioverter-defibrillator kit; and

FIG. 41(b) is a perspective view of a hemostat illustrating the length measurement.

#### DETAILED DESCRIPTION

Turning now to FIG. 1, the S-ICD of the present invention is illustrated. The S-ICD consists of an electrically active canister 11 and a subcutaneous electrode 13 attached to the canister. The canister has an electrically active surface 15 that is electrically insulated from the electrode connector

block 17 and the canister housing 16 via insulating area 14. The canister can be similar to numerous electrically active canisters commercially available in that the canister will contain a battery supply, capacitor and operational circuitry.

5 Alternatively, the canister can be thin and elongated to conform to the intercostal space. The circuitry will be able to monitor cardiac rhythms for tachycardia and fibrillation, and if detected, will initiate charging the capacitor and then delivering cardioversion /defibrillation energy through the active surface of the housing and to the subcutaneous electrode. Examples of such circuitry are described in U.S. Patent Nos. 4,693,253 and 5,105,810, the entire disclosures of which are herein incorporated by reference. The canister circuitry can provide cardioversion/ defibrillation energy in different types of waveforms. In the preferred embodiment, a 100 uF biphasic waveform is used of approximately 10-20 ms total duration and with the initial phase containing approximately 2/3 of the energy, however, any type of waveform can be utilized such as monophasic, biphasic, multiphasic or alternative waveforms as is  
10  
15  
20 known in the art.

In addition to providing cardioversion/ defibrillation energy, the circuitry can also provide transthoracic cardiac pacing energy. The optional circuitry will be able to monitor the heart for bradycardia and/or tachycardia rhythms. Once a

bradycardia or tachycardia rhythm is detected, the circuitry can then deliver appropriate pacing energy at appropriate intervals through the active surface and the subcutaneous electrode. Pacing stimuli will be biphasic in the preferred embodiment and  
5 similar in pulse amplitude to that used for conventional transthoracic pacing.

This same circuitry can also be used to deliver low amplitude shocks on the T-wave for induction of ventricular fibrillation for testing S-ICD performance in treating V-Fib as is described in U.S. Patent No. 5,129,392, the entire disclosure of which is hereby incorporated by reference. Also the circuitry can be provided with rapid induction of ventricular fibrillation or ventricular tachycardia using rapid ventricular pacing. Another optional way for inducing ventricular fibrillation would be to provide a continuous low voltage, i.e., about 3 volts, across the heart during the entire cardiac cycle.

Another optional aspect of the present invention is that the operational circuitry can detect the presence of atrial fibrillation as described in Olson, W. et al. "Onset And  
20 Stability For Ventricular Tachyarrhythmia Detection in an Implantable Cardioverter and Defibrillator," Computers in Cardiology (1986) pp. 167-170. Detection can be provided via R-R Cycle length instability detection algorithms. Once atrial fibrillation has been detected, the operational circuitry will

then provide QRS synchronized atrial  
defibrillation/cardioversion using the same shock energy and  
waveshape characteristics used for ventricular defibrillation/  
cardioversion.

5 The sensing circuitry will utilize the electronic signals  
generated from the heart and will primarily detect QRS waves.  
In one embodiment, the circuitry will be programmed to detect  
only ventricular tachycardias or fibrillations. The detection  
circuitry will utilize in its most direct form, a rate detection  
10 algorithm that triggers charging of the capacitor once the  
ventricular rate exceeds some predetermined level for a fixed  
period of time: for example, if the ventricular rate exceeds  
240 bpm on average for more than 4 seconds. Once the capacitor  
is charged, a confirmatory rhythm check would ensure that the  
15 rate persists for at least another 1 second before discharge.  
Similarly, termination algorithms could be instituted that  
ensure that a rhythm less than 240 bpm persisting for at least 4  
seconds before the capacitor charge is drained to an internal  
resistor. Detection, confirmation and termination algorithms as  
20 are described above and in the art can be modulated to increase  
sensitivity and specificity by examining QRS beat-to-beat  
uniformity, QRS signal frequency content, R-R interval stability  
data, and signal amplitude characteristics all or part of which

can be used to increase or decrease both sensitivity and specificity of S-ICD arrhythmia detection function.

In addition to use of the sense circuitry for detection of V-Fib or V-Tach by examining the QRS waves, the sense circuitry  
5 can check for the presence or the absence of respiration. The respiration rate can be detected by monitoring the impedance across the thorax using subthreshold currents delivered across the active can and the high voltage subcutaneous lead electrode and monitoring the frequency in undulation in the waveform that  
10 results from the undulations of transthoracic impedance during the respiratory cycle. If there is no undulation, then the patient is not respiring and this lack of respiration can be used to confirm the QRS findings of cardiac arrest. The same technique can be used to provide information about the  
15 respiratory rate or estimate cardiac output as described in U.S. Patent Nos. 6,095,987, 5,423,326, 4,450,527, the entire disclosures of which are incorporated herein by reference.

The canister of the present invention can be made out of titanium alloy or other presently preferred electrically active  
20 canister designs. However, it is contemplated that a malleable canister that can conform to the curvature of the patient's chest will be preferred. In this way the patient can have a comfortable canister that conforms to the shape of the patient's rib cage. Examples of conforming canisters are provided in U.S.

Patent No. 5,645,586, the entire disclosure of which is herein incorporated by reference. Therefore, the canister can be made out of numerous materials such as medical grade plastics, metals, and alloys. In the preferred embodiment, the canister is smaller than 60 cc volume having a weight of less than 100 gms for long term wearability, especially in children. The canister and the lead of the S-ICD can also use fractal or wrinkled surfaces to increase surface area to improve defibrillation capability. Because of the primary prevention role of the therapy and the likely need to reach energies over 40 Joules, a feature of the preferred embodiment is that the charge time for the therapy, intentionally is relatively long to allow capacitor charging within the limitations of device size. Examples of small ICD housings are disclosed in U.S. Patents Nos. 5,597,956 and 5,405,363, the entire disclosures of which are herein incorporated by reference.

Different subcutaneous electrodes 13 of the present invention are illustrated in FIGS. 1-3. Turning to FIG. 1, the lead 21 for the subcutaneous electrode is preferably composed of silicone or polyurethane insulation. The electrode is connected to the canister at its proximal end via connection port 19 which is located on an electrically insulated area 17 of the canister. The electrode illustrated is a composite electrode with three different electrodes attached to the lead. In the embodiment



illustrated, an optional anchor segment 52 is attached at the most distal end of the subcutaneous electrode for anchoring the electrode into soft tissue such that the electrode does not dislodge after implantation.

5       The most distal electrode on the composite subcutaneous electrode is a coil electrode 27 that is used for delivering the high voltage cardioversion/ defibrillation energy across the heart. The coil cardioversion/defibrillation electrode is about 5-10 cm in length. Proximal to the coil electrode are two sense electrodes, a first sense electrode 25 is located proximally to the coil electrode and a second sense electrode 23 is located proximally to the first sense electrode. The sense electrodes are spaced far enough apart to be able to have good QRS detection. This spacing can range from 1 to 10 cm with 4 cm being presently preferred. The electrodes may or may not be circumferential with the preferred embodiment. Having the electrodes non-circumferential and positioned outward, toward the skin surface, is a means to minimize muscle artifact and enhance QRS signal quality. The sensing electrodes are  
10 electrically isolated from the cardioversion/defibrillation electrode via insulating areas 29. Similar types of cardioversion/defibrillation electrodes are currently commercially available in a transvenous configuration. For example, U.S. Patent No. 5,534,022, the entire disclosure of  
20

which is herein incorporated by reference, disclosures a composite electrode with a coil cardioversion/defibrillation electrode and sense electrodes. Modifications to this arrangement is contemplated within the scope of the invention.

5 One such modification is illustrated in FIG. 2 where the two sensing electrodes 25 and 23 are non-circumferential sensing electrodes and one is located at the distal end, the other is located proximal thereto with the coil electrode located in between the two sensing electrodes. In this embodiment the sense electrodes are spaced about 6 to about 12 cm apart depending on the length of the coil electrode used. FIG. 3 illustrates yet a further embodiment where the two sensing electrodes are located at the distal end to the composite electrode with the coil electrode located proximally thereto. Other possibilities exist and are contemplated within the present invention. For example, having only one sensing electrode, either proximal or distal to the coil cardioversion/defibrillation electrode with the coil serving as both a sensing electrode and a cardioversion/defibrillation electrode.

20 It is also contemplated within the scope of the invention that the sensing of QRS waves (and transthoracic impedance) can be carried out via sense electrodes on the canister housing or in combination with the cardioversion/defibrillation coil electrode and/or the subcutaneous lead sensing electrode(s). In

this way, sensing could be performed via the one coil electrode located on the subcutaneous electrode and the active surface on the canister housing. Another possibility would be to have only one sense electrode located on the subcutaneous electrode and the sensing would be performed by that one electrode and either the coil electrode on the subcutaneous electrode or by the active surface of the canister. The use of sensing electrodes on the canister would eliminate the need for sensing electrodes on the subcutaneous electrode. It is also contemplated that the subcutaneous electrode would be provided with at least one sense electrode, the canister with at least one sense electrode, and if multiple sense electrodes are used on either the subcutaneous electrode and/or the canister, that the best QRS wave detection combination will be identified when the S-ICD is implanted and this combination can be selected, activating the best sensing arrangement from all the existing sensing possibilities. Turning again to FIG. 2, two sensing electrodes 26 and 28 are located on the electrically active surface 15 with electrical insulator rings 30 placed between the sense electrodes and the active surface. These canister sense electrodes could be switched off and electrically insulated during and shortly after defibrillation/ cardioversion shock delivery. The canister sense electrodes may also be placed on the electrically inactive surface of the canister. In the embodiment of FIG. 2, there are

actually four sensing electrodes, two on the subcutaneous lead and two on the canister. In the preferred embodiment, the ability to change which electrodes are used for sensing would be a programmable feature of the S-ICD to adapt to changes in the patient physiology and size (in the case of children) over time. The programming could be done via the use of physical switches on the canister, or as presently preferred, via the use of a programming wand or via a wireless connection to program the circuitry within the canister.

The canister could be employed as either a cathode or an anode of the S-ICD cardioversion/defibrillation system. If the canister is the cathode, then the subcutaneous coil electrode would be the anode. Likewise, if the canister is the anode, then the subcutaneous electrode would be the cathode.

The active canister housing will provide energy and voltage intermediate to that available with ICDs and most AEDs. The typical maximum voltage necessary for ICDs using most biphasic waveforms is approximately 750 Volts with an associated maximum energy of approximately 40 Joules. The typical maximum voltage necessary for AEDs is approximately 2000-5000 Volts with an associated maximum energy of approximately 200-360 Joules depending upon the model and waveform used. The S-ICD of the present invention uses maximum voltages in the range of about 700 to about 3150 Volts and is associated with energies of about

40 to about 210 Joules. The capacitance of the S-ICD could range from about 50 to about 200 micro farads.

5 The sense circuitry contained within the canister is highly sensitive and specific for the presence or absence of life threatening ventricular arrhythmias. Features of the detection algorithm are programmable and the algorithm is focused on the detection of V-FIB and high rate V-TACH (>240 bpm). Although the S-ICD of the present invention may rarely be used for an actual life threatening event, the simplicity of design and implementation allows it to be employed in large populations of patients at modest risk with modest cost by non-cardiac electrophysiologists. Consequently, the S-ICD of the present invention focuses mostly on the detection and therapy of the most malignant rhythm disorders. As part of the detection algorithm's applicability to children, the upper rate range is programmable upward for use in children, known to have rapid supraventricular tachycardias and more rapid ventricular fibrillation. Energy levels also are programmable downward in order to allow treatment of neonates and infants.

20 Turning now to FIG. 4, the optimal subcutaneous placement of the S-ICD of the present invention is illustrated. As would be evidence to a person skilled in the art, the actual location of the S-ICD is in a subcutaneous space that is developed during the implantation process. The heart is not exposed during this

process and the heart is schematically illustrated in the figures only for help in understanding where the canister and coil electrode are three dimensionally located in the left mid-clavicular line approximately at the level of the inframammary crease at approximately the 5th rib. The lead 21 of the subcutaneous electrode traverses in a subcutaneous path around the thorax terminating with its distal electrode end at the posterior axillary line ideally just lateral to the left scapula. This way the canister and subcutaneous cardioversion/defibrillation electrode provide a reasonably good pathway for current delivery to the majority of the ventricular myocardium.

FIG. 5 illustrates a different placement of the present invention. The S-ICD canister with the active housing is located in the left posterior axillary line approximately lateral to the tip of the inferior portion of the scapula. This location is especially useful in children. The lead 21 of the subcutaneous electrode traverses in a subcutaneous path around the thorax terminating with its distal electrode end at the anterior precordial region, ideally in the inframammary crease.

FIG. 6 illustrates the embodiment of FIG. 1 subcutaneously implanted in the thorax with the proximal sense electrodes 23 and 25 located at approximately the left axillary line with the

cardioversion/defibrillation electrode just lateral to the tip of the inferior portion of the scapula.

FIG. 7 schematically illustrates the method for implanting the S-ICD of the present invention. An incision 31 is made in the left anterior axillary line approximately at the level of the cardiac apex. This incision location is distinct from that chosen for S-ICD placement and is selected specifically to allow both canister location more medially in the left inframammary crease and lead positioning more posteriorly via the introducer set (described below) around to the left posterior axillary line lateral to the left scapula. That said, the incision can be anywhere on the thorax deemed reasonably by the implanting physician although in the preferred embodiment, the S-ICD of the present invention will be applied in this region. A subcutaneous pathway 33 is then created medially to the inframmary crease for the canister and posteriorly to the left posterior axillary line lateral to the left scapula for the lead.

The S-ICD canister 11 is then placed subcutaneously at the location of the incision or medially at the subcutaneous region at the left inframmary crease. The subcutaneous electrode 13 is placed with a specially designed curved introducer set 40 (see FIG. 8). The introducer set comprises a curved trocar 42 and a stiff curved peel away sheath 44. The peel away sheath is

curved to allow for placement around the rib cage of the patient in the subcutaneous space created by the trocar. The sheath has to be stiff enough to allow for the placement of the electrodes without the sheath collapsing or bending. Preferably the sheath is made out of a biocompatible plastic material and is perforated along its axial length to allow for it to split apart into two sections. The trocar has a proximal handle 41 and a curved shaft 43. The distal end 45 of the trocar is tapered to allow for dissection of a subcutaneous path 33 in the patient. Preferably, the trocar is cannulated having a central Lumen 46 and terminating in an opening 48 at the distal end. Local anesthetic such as lidocaine can be delivered, if necessary, through the lumen or through a curved and elongated needle designed to anesthetize the path to be used for trocar insertion should general anesthesia not be employed. The curved peel away sheath 44 has a proximal pull tab 49 for breaking the sheath into two halves along its axial shaft 47. The sheath is placed over a guidewire inserted through the trocar after the subcutaneous path has been created. The subcutaneous pathway is then developed until it terminates subcutaneously at a location that, if a straight line were drawn from the canister location to the path termination point the line would intersect a substantial portion of the left ventricular mass of the patient. The guidewire is then removed leaving the peel away sheath. The



subcutaneous lead system is then inserted through the sheath until it is in the proper location. Once the subcutaneous lead system is in the proper location, the sheath is split in half using the pull tab 49 and removed. If more than one subcutaneous electrode is being used, a new curved peel away sheath can be used for each subcutaneous electrode.

The S-ICD will have prophylactic use in adults where chronic transvenous/epicardial ICD lead systems pose excessive risk or have already resulted in difficulty, such as sepsis or lead fractures. It is also contemplated that a major use of the S-ICD system of the present invention will be for prophylactic use in children who are at risk for having fatal arrhythmias, where chronic transvenous lead systems pose significant management problems. Additionally, with the use of standard transvenous ICDs in children, problems develop during patient growth in that the lead system does not accommodate the growth. FIG. 9 illustrates the placement of the S-ICD subcutaneous lead system such that the problem that growth presents to the lead system is overcome. The distal end of the subcutaneous electrode is placed in the same location as described above providing a good location for the coil cardioversion/defibrillation electrode 27 and the sensing electrodes 23 and 25. The insulated lead 21, however is no longer placed in a taught configuration. Instead, the lead is

serpigginously placed with a specially designed introducer trocar and sheath such that it has numerous waves or bends. As the child grows, the waves or bends will straighten out lengthening the lead system while maintaining proper electrode placement.

5 Although it is expected that fibrous scarring especially around the defibrillation coil will help anchor it into position to maintain its posterior position during growth, a lead system with a distal tine or screw electrode anchoring system 52 can also be incorporated into the distal tip of the lead to facilitate lead stability (see FIG. 1). Other anchoring systems can also be used such as hooks, sutures, or the like.

FIGS. 10 and 11 illustrate another embodiment of the present S-ICD invention. In this embodiment there are two subcutaneous electrodes 13 and 13' of opposite polarity to the canister. The additional subcutaneous electrode 13' is essentially identical to the previously described electrode. In this embodiment the cardioversion/defibrillation energy is delivered between the active surface of the canister and the two coil electrodes 27 and 27'. Additionally, provided in the canister is means for selecting the optimum sensing arrangement between the four sense electrodes 23, 23', 25, and 25'. The two electrodes are subcutaneously placed on the same side of the heart. As illustrated in FIG. 6, one subcutaneous electrode 13 is placed inferiorly and the other electrode 13' is placed

superiorly. It is also contemplated with this dual subcutaneous electrode system that the canister and one subcutaneous electrode are the same polarity and the other subcutaneous electrode is the opposite polarity.

5 Turning now to FIGS. 12 and 13, further embodiments are illustrated where the canister 11 of the S-ICD of the present invention is shaped to be particularly useful in placing subcutaneously adjacent and parallel to a rib of a patient. The canister is long, thin, and curved to conform to the shape of the patient's rib. In the embodiment illustrated in FIG. 12, the canister has a diameter ranging from about 0.5 cm to about 2 cm without 1 cm being presently preferred. Alternatively, instead of having a circular cross sectional area, the canister could have a rectangular or square cross sectional area as illustrated in FIG. 13 without falling outside of the scope of the present invention. The length of the canister can vary depending on the size of the patient's thorax. Currently the canister is about 5 cm to about 15 cm long with about 10 being presently preferred. The canister is curved to conform to the curvature of the ribs of the thorax. The radius of the curvature will vary depending on the size of the patient, with smaller radiuses for smaller patients and larger radiuses for larger patients. The radius of the curvature can range from about 5 cm to about 35 cm depending on the size of the patient.

Additionally, the radius of the curvature need not be uniform throughout the canister such that it can be shaped closer to the shape of the ribs. The canister has an active surface, 15 that is located on the interior (concave) portion of the curvature and an inactive surface 16 that is located on the exterior (convex) portion of the curvature. The leads of these embodiments, which are not illustrated except for the attachment port 19 and the proximal end of the lead 21, can be any of the leads previously described above, with the lead illustrated in FIG. 1 being presently preferred.

The circuitry of this canister is similar to the circuitry described above. Additionally, the canister can optionally have at least one sense electrode located on either the active surface of the inactive surface and the circuitry within the canister can be programmable as described above to allow for the selection of the best sense electrodes. It is presently preferred that the canister have two sense electrodes 26 and 28 located on the inactive surface of the canisters as illustrated, where the electrodes are spaced from about 1 to about 10 cm apart with a spacing of about 3 cm being presently preferred. However, the sense electrodes can be located on the active surface as described above.

It is envisioned that the embodiment of FIG. 12 will be subcutaneously implanted adjacent and parallel to the left

anterior 5th rib, either between the 4th and 5th ribs or between the 5th and 6th ribs. However other locations can be used.

Another component of the S-ICD of the present invention is a cutaneous test electrode system designed to simulate the subcutaneous high voltage shock electrode system as well as the QRS cardiac rhythm detection system. This test electrode system is comprised of a cutaneous patch electrode of similar surface area and impedance to that of the S-ICD canister itself together with a cutaneous strip electrode comprising a defibrillation strip as well as two button electrodes for sensing of the QRS. Several cutaneous strip electrodes are available to allow for testing various bipole spacings to optimize signal detection comparable to the implantable system.

Figures 14 to 18 depict particular US-ICD embodiments of the present invention. The various sensing, shocking and pacing circuitry, described in detail above with respect to the S-ICD embodiments, may additionally be incorporated into the following US-ICD embodiments. Furthermore, particular aspects of any individual S-ICD embodiment discussed above, may be incorporated, in whole or in part, into the US-ICD embodiments depicted in the following figures.

Turning now to Fig. 14, the US-ICD of the present invention is illustrated. The US-ICD consists of a curved housing 1211 with a first and second end. The first end 1413 is thicker than

the second end 1215. This thicker area houses a battery supply, capacitor and operational circuitry for the US-ICD. The circuitry will be able to monitor cardiac rhythms for tachycardia and fibrillation, and if detected, will initiate  
5 charging the capacitor and then delivering cardioversion/defibrillation energy through the two cardioversion/defibrillating electrodes 1417 and 1219 located on the outer surface of the two ends of the housing. The circuitry can provide cardioversion/defibrillation energy in different types of waveforms. In the preferred embodiment, a 100 uF biphasic waveform is used of approximately 10-20 ms total duration and with the initial phase containing approximately 2/3 of the energy, however, any type of waveform can be utilized such as monophasic, biphasic, multiphasic or alternative waveforms as is known in the art.

The housing of the present invention can be made out of titanium alloy or other presently preferred ICD designs. It is contemplated that the housing is also made out of biocompatible plastic materials that electronically insulate the electrodes  
20 from each other. However, it is contemplated that a malleable canister that can conform to the curvature of the patient's chest will be preferred. In this way the patient can have a comfortable canister that conforms to the unique shape of the patient's rib cage. Examples of conforming ICD housings are

provided in U.S. Patent No. 5,645,586, the entire disclosure of which is herein incorporated by reference. In the preferred embodiment, the housing is curved in the shape of a 5<sup>th</sup> rib of a person. Because there are many different sizes of people, the housing will come in different incremental sizes to allow a good match between the size of the rib cage and the size of the US-ICD. The length of the US-ICD will range from about 15 to about 50 cm. Because of the primary preventative role of the therapy and the need to reach energies over 40 Joules, a feature of the preferred embodiment is that the charge time for the therapy, intentionally be relatively long to allow capacitor charging within the limitations of device size.

The thick end of the housing is currently needed to allow for the placement of the battery supply, operational circuitry, and capacitors. It is contemplated that the thick end will be about 0.5 cm to about 2 cm wide with about 1 cm being presently preferred. As microtechnology advances, the thickness of the housing will become smaller.

The two cardioversion/defibrillation electrodes on the housing are used for delivering the high voltage cardioversion/defibrillation energy across the heart. In the preferred embodiment, the cardioversion/defibrillation electrodes are coil electrodes, however, other cardioversion/defibrillation electrodes could be used such as

having electrically isolated active surfaces or platinum alloy electrodes. The coil cardioversion/defibrillation electrodes are about 5-10 cm in length. Located on the housing between the two cardioversion/defibrillation electrodes are two sense electrodes 1425 and 1427. The sense electrodes are spaced far enough apart to be able to have good QRS detection. This spacing can range from 1 to 10 cm with 4 cm being presently preferred. The electrodes may or may not be circumferential with the preferred embodiment. Having the electrodes non-circumferential and positioned outward, toward the skin surface, is a means to minimize muscle artifact and enhance QRS signal quality. The sensing electrodes are electrically isolated from the cardioversion/defibrillation electrode via insulating areas 1423. Analogous types of cardioversion/defibrillation electrodes are currently commercially available in a transvenous configuration. For example, U.S. Patent No. 5,534,022, the entire disclosure of which is herein incorporated by reference, discloses a composite electrode with a coil cardioversion/defibrillation electrode and sense electrodes. Modifications to this arrangement is contemplated within the scope of the invention. One such modification is to have the sense electrodes at the two ends of the housing and have the cardioversion/defibrillation electrodes located in between the sense electrodes. Another modification is to have three or more



sense electrodes spaced throughout the housing and allow for the selection of the two best sensing electrodes. If three or more sensing electrodes are used, then the ability to change which electrodes are used for sensing would be a programmable feature of the US-ICD to adapt to changes in the patient physiology and size over time. The programming could be done via the use of physical switches on the canister, or as presently preferred, via the use of a programming wand or via a wireless connection to program the circuitry within the canister.

Turning now to Fig. 15, the optimal subcutaneous placement of the US-ICD of the present invention is illustrated. As would be evident to a person skilled in the art, the actual location of the US-ICD is in a subcutaneous space that is developed during the implantation process. The heart is not exposed during this process and the heart is schematically illustrated in the figures only for help in understanding where the device and its various electrodes are three dimensionally located in the thorax of the patient. The US-ICD is located between the left mid-clavicular line approximately at the level of the inframammary crease at approximately the 5<sup>th</sup> rib and the posterior axillary line, ideally just lateral to the left scapula. This way the US-ICD provides a reasonably good pathway for current delivery to the majority of the ventricular myocardium.

Fig. 16 schematically illustrates the method for implanting the US-ICD of the present invention. An incision 1631 is made in the left anterior axillary line approximately at the level of the cardiac apex. A subcutaneous pathway is then created that extends posteriorly to allow placement of the US-ICD. The incision can be anywhere on the thorax deemed reasonable by the implanting physician although in the preferred embodiment, the US-ICD of the present invention will be applied in this region. The subcutaneous pathway is created medially to the inframammary crease and extends posteriorly to the left posterior axillary line. The pathway is developed with a specially designed curved introducer 1742 (see Fig. 17). The trocar has a proximal handle 1641 and a curved shaft 1643. The distal end 1745 of the trocar is tapered to allow for dissection of a subcutaneous path in the patient. Preferably, the trocar is cannulated having a central lumen 1746 and terminating in an opening 1748 at the distal end. Local anesthetic such as lidocaine can be delivered, if necessary, through the lumen or through a curved and elongated needle designed to anesthetize the path to be used for trocar insertion should general anesthesia not be employed. Once the subcutaneous pathway is developed, the US-ICD is implanted in the subcutaneous space, the skin incision is closed using standard techniques.

As described previously, the US-ICDs of the present invention vary in length and curvature. The US-ICDs are provided in incremental sizes for subcutaneous implantation in different sized patients. Turning now to Fig. 18, a different embodiment is schematically illustrated in exploded view which provides different sized US-ICDs that are easier to manufacture. The different sized US-ICDs will all have the same sized and shaped thick end 1413. The thick end is hollow inside allowing for the insertion of a core operational member 1853. The core member comprises a housing 1857 which contains the battery supply, capacitor and operational circuitry for the US-ICD. The proximal end of the core member has a plurality of electronic plug connectors. Plug connectors 1861 and 1863 are electronically connected to the sense electrodes via pressure fit connectors (not illustrated) inside the thick end which are standard in the art. Plug connectors 1865 and 1867 are also electronically connected to the cardioverter/defibrillator electrodes via pressure fit connectors inside the thick end. The distal end of the core member comprises an end cap 1855, and a ribbed fitting 1859 which creates a water-tight seal when the core member is inserted into opening 1851 of the thick end of the US-ICD.

The core member of the different sized and shaped US-ICD will all be the same size and shape. That way, during an

implantation procedures, multiple sized US-ICDs can be available for implantation, each one without a core member. Once the implantation procedure is being performed, then the correct sized US-ICD can be selected and the core member can be inserted  
5 into the US-ICD and then programmed as described above. Another advantage of this configuration is when the battery within the core member needs replacing it can be done without removing the entire US-ICD.

FIG. 14(a) illustrates an embodiment of the subcutaneous lead electrode or "lead electrode assembly" 100. The lead electrode assembly 100 is designed to provide an electrode 107 to be implanted subcutaneously in the posterior thorax of a patient for delivery of cardioversion/defibrillation energy. The lead electrode assembly 100 is further designed to provide a path for the cardioversion/defibrillation energy to reach the electrode 107 from the operational circuitry within the canister 11 of an S-ICD such as the embodiment shown in FIG. 1.

The lead electrode assembly 100 comprises a connector 111, a lead 21, a lead fastener 146, an electrode 107 and an  
20 appendage 118. The connector 111 is connected to the lead 21. The lead 21 is further connected to the electrode 107 with the lead fastener 146. The appendage 118 is mounted to the electrode 107.

The connector 111 provides an electrical connection between the lead 21 and the operational circuitry within the canister 11 of an S-ICD such as the embodiment shown in FIG. 1. Connector 111 is designed to mate with the connection port 19 on the canister 11. In the embodiment under discussion, the connector 111 meets the IS-1 standard.

The lead 21 of the lead electrode assembly 100 provides an electrical connection between the connector 111 and the electrode 107. The lead 21 comprises a distal end 101 and a proximal end 102. The distal end 101 of the lead 21 is attached to the connector 111. The proximal end 102 of the lead 21 is attached to electrode 107 with the lead fastener 146.

The lead 21 has a lead length,  $l_{\text{Lead}}$ , measured from the connector 111 along the lead 21 to the lead fastener 146 of the electrode 107. The length of the lead 21 is approximately 25 cm. In alternative embodiments, the lead lengths range between approximately 5 cm and approximately 52 cm.

The lead fastener 146 provides a robust physical and electrical connection between the lead 21 and the electrode 107. The lead fastener 146 joins the proximal end 102 of the lead 21 to electrode 107.

The electrode 107 comprises an electrically conductive member designed to make contact with the tissue of the patient

and transfer cardioversion/defibrillation energy to the tissue of the patient from the S-ICD canister 11.

The electrode 107 illustrated is generally flat and planar, comprising a top surface 110, a bottom surface 115, a distal end 103 and a proximal end 104. The lead fastener 146 is attached to the top surface 110 of the distal end 103 of the electrode 107.

The electrode 107 may have shapes other than planar. In an alternate embodiment, the electrode 107 is shaped like a coil.

The appendage 118 is a member attached to the electrode 107 that can be gripped and used to precisely locate the lead electrode assembly 100 during its surgical implantation within the patient.

The appendage 118 has a first end 105, a second end 106, a distal edge 121 and a proximal edge 129. The second end 106 of the appendage 118 is attached to the top surface 110 of the electrode 107. The appendage 118 is positioned such that its proximal edge 129 is within approximately 20 mm of the proximal end 104 of the electrode 107. In alternate embodiments, the appendage 118 is attached to the electrode 107 in other positions.

It is useful at this point, to set out several general definitions for future reference in discussing the dimensions and placement of appendages 118.

The appendage height,  $h_{\text{Appendage}}$ , is defined as the distance from the point of the appendage 118 most distant from the electrode 107 to a point of the appendage 118 closest to the electrode 107 measured along a line perpendicular to the top surface 110 of the electrode 107. The appendage height of the appendage 118 illustrated, for example, would be measured between the first end 105 of the appendage 118 and the second end 106 of the appendage 118.

The appendage height of the appendage 118 illustrated is approximately 5 mm. In alternative embodiments, the appendage heights range between approximately 1 mm and approximately 10 mm.

The appendage interface is defined as the part of the appendage 118 that joins it to the electrode 107. The appendage interface of the appendage 118 illustrated, for example, would be the second end 106 of the appendage 118.

The appendage length,  $l_{\text{Appendage}}$ , is the length of the appendage 118 along the appendage interface. The appendage interface of the appendage 118 illustrated, for example, would be the length of the second end 106 of the appendage 118.

The appendage length of the appendage 118 illustrated in FIG. 14 is approximately 1 cm. In alternative embodiments, appendage lengths range between approximately 2 mm and

approximately 6 cm. In an alternate embodiment, the appendage 118 is substantially as long as the electrode 107.

More particularly, the appendage 118 of the embodiment illustrated is a fin 120 comprising a fin core 122 (phantom view) and a coating 125.

The fin core 122 generally provides support for the fin 120. The fin core 122 has a first end 126 and a second end 127. The second end 127 of the fin core 122 is attached to the top surface 110 of the electrode 107.

The fin core 122 comprises a metal selected from the group consisting essentially of titanium, nickel alloys, stainless steel alloys, platinum, platinum iridium, and mixtures thereof. In other embodiments, the fin core 122 comprises any rugged material that can be attached to the first surface 110 of the electrode 107.

The coating 125 is disposed around the fin core 122. The coating 125 provides a surface for the fin 120 that can be easily gripped during the implantation of the lead electrode assembly 100. The coating 125 covering the fin core 122 is composed of molded silicone. In an alternative embodiment, the coating 125 may be any polymeric material. In this specification, the term polymeric material includes the group of materials consisting of a polyurethane, a polyamide, a



polyeteretherketone (PEEK), a polyether block amide (PEBA), a polytetrafluoroethylene (PTFE), a silicone and mixtures thereof.

In one embodiment, the fin 120 is reinforced with a layer of Dacron<sup>®</sup> polymer mesh attached to the inside of the coating 125. Dacron<sup>®</sup> is a registered trademark of E.I. du Pont de Nemours and Company Corporation, Wilmington, DE. In another embodiment, the Dacron<sup>®</sup> polymer mesh attached to the outside of the coating 125. In another embodiment, the fin 120 is reinforced with a layer of any polymeric material.

FIG. 14(b) illustrates a top view of the lead electrode assembly 100. The electrode 107 is substantially rectangular in shape, comprising a first pair of sides 108, a second pair of sides 109 and four corners 112. In an alternative embodiment the electrode 107 has a shape other than rectangular. In this embodiment, the corners 112 of the electrode 107 are rounded. In an alternative embodiment the corners 112 of the electrode 107 are not rounded.

The first pair of sides 108 of the electrode 107 are substantially linear, substantially parallel to each other and are approximately 1 cm in length. The second pair of sides 109 of the electrode 107 are also substantially linear, substantially parallel with each other and are approximately 5 cm in length. The bottom surface 115 of the electrode 107 has an area of approximately 500 square mm. In alternative

embodiments, the first pair of sides 108 and the second pair of sides 109 of the electrode 107 are neither linear nor parallel.

In alternative embodiments, the length of the first pair of sides 108 and second pair of sides 109 of the electrode 107 range independently between approximately 1 cm and approximately 5 cm. The surface area of the bottom surface 115 of the electrode 107 ranges between approximately 100 sq. mm and approximately 2000 sq. mm. In one embodiment, the first pair of sides 108 and second pair of sides 109 of the electrode 107 are linear and of equal length, such that the electrode 107 is substantially square-shaped.

The electrode 107 comprises a sheet of metallic mesh 114 further comprised of woven wires 119. The metallic mesh 114 comprises a metal selected from the group consisting essentially of titanium, nickel alloys, stainless steel alloys, platinum, platinum iridium, and mixtures thereof. In other embodiments, the metallic mesh 114 comprises any conductive material.

In an alternate embodiment, the electrode 107 comprises a solid metallic plate. The metallic plate comprises a metal selected from the group consisting essentially of titanium, nickel alloys, stainless steel alloys, platinum, platinum iridium, and mixtures thereof. In other embodiments, the solid plate comprises any conductive material.

The metallic mesh 114 is approximately a 150 mesh, having approximately 150 individual wires 119 per inch. In alternative embodiments, the metallic mesh 114 ranges between approximately a 50 mesh and approximately a 200 mesh. In this embodiment, the diameter of the wires 119 of the mesh is approximately 1 mil. In alternative embodiments, the diameter of the wires 119 ranges between approximately 1 and approximately 5 mils.

The metallic mesh 114 is first prepared by spot welding together the wires 119 located along the first pair of sides 108 and second pair of sides 109 of the metallic mesh 114. The excess lengths of wires are then ground or machined flush, so as to produce a smooth edge and to form a smooth border 113. In an alternate embodiment, the wires 119 located along the first pair of sides 108 and second pair of sides 109 of the metallic mesh 114 are bent in toward the metallic mesh 114 to form a smooth border 113.

The fin 120 is attached to the top surface 110 of the electrode 107 in a position centered between the first pair of sides 108 of the electrode 107. In other embodiments, the fin 120 is not centered between the first pair of sides 108 of the electrode 107.

The fin 120 is planar shape comprising a first face 191 and a second face 192. The first face 191 and the second face 192 of the fin 120 are substantially parallel to the first pair of

sides 108 of the electrode 107. In other embodiments, the first face 191 and the second face 192 of the fin 120 are positioned in orientations other than parallel to the first pair of sides 108 of the electrode 107.

5 The first face 191 and the second face 192 of the fin 120 extend from and substantially perpendicular to the top surface 110 of the electrode 107. In an alternative embodiment, the first face 191 and the second face 192 of the fin 120 extend from the top surface 110 of the electrode 107 at other than right angles.

10 The fin core 122 of the fin 120 is spot welded to the metallic mesh 114 comprising the electrode 107. In another embodiment, the fin 120 may be composed entirely of a polymeric material and attached to the electrode 107 by means known in the art.

15 FIG. 14(c) illustrates in detail a section of the lead 21 of this embodiment. The lead 21 comprises an electrically insulating sheath 141 and an electrical conductor 142.

20 The electrically insulating sheath 141 is disposed around the electrical conductor 142 (phantom view). The electrically insulating sheath 141 prevents the cardioversion/defibrillation energy passing through the electrical conductor 142 to the electrode from passing into objects surrounding the lead 21. The electrically insulating sheath 141, comprises a tube 149

disposed around the electrical conductor 142. The tube is composed of either silicone, polyurethane or composite materials. One skilled in the art will recognize that the tube 149 could alternately be composed of any insulating, flexible, 5 bio-compatible material suitable to this purpose.

In this embodiment, the electrical conductor 142 comprises three highly-flexible, highly-conductive coiled fibers known as filars 147 (phantom view). These fibers are wound in a helical shape through the electrically insulating sheath 141. In an alternate embodiment, the filars lie as linear cables within the electrically insulating sheath 141. In another alternate embodiment, a combination of helically coiled and linear filars lie within the electrically insulating sheath 141.

FIG. 14(d) illustrates a cross-section of a filar 147. The filars 147 of the embodiment illustrated comprise a metal core 144, a metal tube 143 and an insulating coating 140. The metal tube 143 is disposed around the metal core 144. The insulating coating 140 is disposed around the metal tube. The metal core 144 is made of silver and the metal tube 143 is made of MP35N<sup>®</sup> 20 stainless steel, a product of SPS Technologies of Jenkintown, PA. The insulating coating 140 is made of teflon. The filars 147 of this structure are available as DFT<sup>™</sup> (drawn filled tube) conductor coil, available from Fort Wayne Metals Research Products Corp. of Fort Wayne, Indiana.

In an alternative embodiment, the filars 147 further comprise an intermediate coating (not shown) disposed between the metal tube 143 and the insulating coating 140. This intermediate coating is made of platinum, iridium ruthenium, 5 palladium or an alloy of these metals.

In another alternative embodiment, the filars 147 comprise DBS™ (drawn braised strands) also available from Fort Wayne Metals Research Products Corp. of Fort Wayne, Indiana.

Turning now to FIG. 14(e), a cross section of the lead fastener 146 is shown in detail. The lead fastener 146 provides a robust physical and electrical connection between the lead 21 and the electrode 107.

In this embodiment, the lead fastener 146 comprises a metal strip 157, a crimping tube 154 and a crimping pin 156. The metal strip 157 has a first end 150, a second end 151, and a middle portion 152. The first end 150 and second end 151 of the metal strip 157 are separated by the middle portion 152. The first end 150 and second end 151 of the metal strip 157 are attached to the electrode 107. In this embodiment, the first 20 end 150 and second end 151 of the lead fastener 146 are spot welded to the top surface 110 of the metallic mesh 114 comprising the electrode 107. In other embodiments, other fastening methods known in the art can be used.

The middle portion 152 of the metal strip 157 is raised away from the electrode 107 to permit the crimping tube 154 and electrically insulating sheath 141 of the lead 21 to fit between the metal strip 157 and the electrode 107.

5       The middle portion 152 of the metal strip 157 contains a crimp point 148. The crimp point 148 squeezes the crimping tube 154 and electrically insulating sheath 141 of the lead 21 thereby gripping it, and thereby providing a robust structural connection between the lead 21 and the electrode 107.

10       The filars 147 of the lead 21 are situated between the crimping tube 154 and crimping pin 156. The crimping tube 154 has a crimping point 155 which causes the filars 147 to be squeezed between crimping tube 154 and crimping pin 156. A gap 159 in the electrically insulating sheath 141 allows the crimping tube 155 to make contact the electrode 107, thereby forming a robust electrical connection.

15       The metal strip 157, the crimping tube 154 and crimping pin 156 are each made of platinum iridium. In an alternative embodiment, the metal strip 157, crimping tube 154 and crimping  
20       pin 156 are each made of a metal selected from the group consisting essentially of titanium, nickel alloys, stainless steel alloys, platinum, platinum iridium, and mixtures thereof. In an alternative embodiment, the metal strip 157, crimping tube

154 and crimping pin 156 are each made of any conductive material.

FIG. 14(f) illustrates an exploded view of the lead fastener 146. In other embodiments, other types of lead fasteners 146 known in the art are used.

FIG. 15(a) illustrates an alternative embodiment of the lead electrode assembly 100. This embodiment is substantially similar to the lead electrode assembly 100 illustrated in FIGS. 14(a)- 14(f). In this embodiment, however, the appendage 118 lacks a fin core 122. Moreover, as seen in FIG. 15(a) the lead electrode assembly 100 of this embodiment further comprises a backing layer 130 and stitching 139. The backing layer 130 acts to insulate the electrode 107 so that cardioversion /defibrillation energy may not pass to the tissue of the patient that surrounds the top surface 110 of the electrode 107. This has the effect of focusing the cardioversion/defibrillation energy toward the heart of the patient through the bottom surface 115 of the electrode 107.

The backing layer 130 comprises a base portion 158 and an integrated fin 120. The base portion 158 of the backing layer 130 comprises a first surface 131, a second surface 132, a first side 133 and a second side 134.

The base portion 158 of the backing layer 130 is attached to the electrode 107 such that the second surface 132 of the



backing layer 130 lies directly adjacent to the top surface 110 of the electrode 107.

The base portion 158 of the backing layer 130 is formed so that the first side 133 and the second side 134 are substantially parallel and of substantially the same size as the first pair of sides 108 of the electrode 107.

FIG. 15(b) illustrates a top view of the lead electrode assembly 100 of this embodiment. The base portion 158 of the backing layer 130 further comprises a distal end 137 and a proximal end 138.

The distal end 137 and proximal end 138 of the backing layer 130 are parallel to and of substantially the same size as the second pair of sides 109 (hidden) of the electrode 107. The backing layer 130 contains a notch 136 on its distal end 137, through which the lead fastener 146 rises.

The base portion 158 of the backing layer 130 is attached to the electrode 107 with stitching 139. The stitching is composed of nylon. In alternate embodiments, the stitching is composed of any polymeric material.

The backing layer 130 is composed of polyurethane. In an alternative embodiment, the backing layer is composed of molded silicone, nylon, or Dacron®. In alternative embodiments, the backing layer is composed of any polymeric material.

The integrated fin 120 of the backing layer 130 is formed from the same piece of material as the backing layer 130. The integrated fin 120 has the same shape and dimensions as the fin 120 of the embodiment in FIG. 14.

5 In one embodiment, the integrated fin 120 is reinforced with a layer of Dacron® polymer mesh attached to the integrated fin 120. In another embodiment, the integrated fin 120 is reinforced with a layer of any polymeric material.

FIG. 16(a) illustrates an alternative embodiment of the lead electrode assembly 100. This embodiment is substantially similar to the lead electrode assembly 100 illustrated in FIGS. 14(a)-14(e). In this embodiment, however, the fin 120 has a different construction.

Here, fin 120 comprises a first fin section 165, a second fin section 160 and stitching 168. The first fin section 165 is a rectangular sheet of polymeric material comprising an inside face 167, an outside face 166, a first side 175 and a second side 174. The first side 175 and second side 174 of the first fin section 165 are substantially parallel and of substantially  
20 the same size.

A line 173 divides the first fin section 165 into a first half 171 and a second half 172. The line 173 runs parallel to the first side 175 of the first fin section 165. The first half 171 of the first fin section 165 lies on one side of line 173.

The second half 172 of the first fin section 165 lies on the other side of the line 173.

The second fin section 160 is a rectangular sheet of polymeric material of the same size as the first fin section 165 comprising an inside face 162 and an outside face 161. The second fin section 160 is divided in half substantially similarly to the first fin section 165, thereby forming a first half 163 and a second half 164 of the second fin section 160.

In an alternate embodiment, the first fin section 165 and second fin section are not rectangular in shape. In an alternate embodiment, the first fin section 165 and second fin section have an oval shape.

The first half 171 of the first fin section 165 is fastened to the first half 163 of the second fin section 160. The inside face 167 of the first half 171 of the first fin section 165 faces the inside face 162 of the first half 163 of the second fin section 160. The first fin section 165 is fastened the second fin section 160 with stitching 168.

The fin 120 is attached to the top surface 110 of the electrode 107. To accomplish this, the second half 172 of the first fin section 165 is attached to the top surface 110 of the electrode 107 with the stitching 169. The second half 164 of the second fin section 160 is similarly attached to the top surface 110 of the electrode 107 with stitching (not shown).

In one embodiment, the fin 120 is reinforced with a layer of Dacron® polymer mesh positioned between the first fin section 165 and the second fin section 160 of the integrated fin 120. In another embodiment, the Dacron® polymer mesh is attached only to the first fin section 165 or the second fin section 160. In other embodiments, the integrated fin 120 is reinforced with a layer of any polymeric material attached to either or both fin sections.

The appendage height of the fin 120 in this embodiment is approximately 5 mm. In alternative embodiments, the appendage heights range between approximately 1 mm and approximately 10 mm. The appendage length of the fin 120 in this embodiment is approximately 1 cm. In alternative embodiments, appendage lengths range between approximately 2 mm and approximately 6 cm. In one embodiment, the appendage length of the fin 120 is such that the fin 120 is substantially as long as the electrode 107.

FIG. 17(a) illustrates a side plan view of an alternative embodiment of the lead electrode assembly 100. The lead electrode assembly 100 comprises a connector 111, a lead 21, a lead fastener 146, an electrode 107, a backing layer 130 with an integrated fin tab 180, a molded cover 220 and an appendage 118.

The connector 111 is connected to the lead 21. The lead 21 is further connected to the electrode 107 with the lead fastener 146. The backing layer 130 is positioned over the electrode

107. The fin tab 180 protrudes from the backing layer 130. The molded cover 220 is disposed around the lead fastener 146 and the backing layer 130. The molded cover 220 is further disposed around the fin tab 180 of the backing layer 118 to form the appendage 118. The molded cover 220 also partially envelops the electrode 107.

The connector 111 and the lead 21 are substantially similar to the connector 111 and the lead 21 described with reference to FIGS. 14(a)-14(f). The lead comprises a distal end 101 and a proximal end 102. The distal end 101 of the lead 21 is attached to the connector 111. The proximal end 102 of the lead 21 is connected to the electrode 107 by the lead fastener 146.

In this embodiment, the lead fastener 146 comprises a first crimping tube 200, a crimping pin 202 and a second crimping tube 201. The first crimping tube 200 connects the proximal end 102 of the lead 21 to the crimping pin 202. The second crimping tube 201 connects the crimping pin 202 to the electrode 107.

The electrode 107 comprises a distal end 103 (phantom view), a proximal end 104, a top surface 110 and a bottom surface 115. The electrode further comprises three sections: a main body 217, a mandrel 219 and a mandrel neck 218.

The main body 217 of the electrode 107 is the region of the electrode 107 that makes contact with the tissue of the patient and transfers the cardioversion/defibrillation energy to the

patient. This region is substantially rectangular, comprising a first pair of sides 108 (not shown) and a second pair of sides 109. The first pair of sides 108 of the electrode 107 are substantially parallel to each other. The second pair of sides 109 of the electrode 107 are also substantially parallel to each other. In another embodiment, the first pair of sides 108 and the second pair of sides 109 of the electrode 107 are non-parallel. The main body 217 of the electrode 107 is positioned under the backing layer 130, so that the top surface 110 of the electrode faces the backing layer 130.

The mandrel 219 is a region of the electrode 107 shaped to facilitate the connection of the electrode 107 to the lead 21 via the lead fastener 146. The mandrel of the electrode is crimped onto to the crimping pin 202 of the lead fastener 146 with the second crimping tube 201, so that a robust physical and electrical connection is formed. The main body 217 of the electrode 107 is connected to the mandrel 219 of the electrode 107 via the mandrel neck 218 of the electrode 107.

The backing layer 130 comprises a base portion 158 and an integrated fin tab 180. The base portion 158 of the backing layer 130 comprises a first surface 131, a second surface 132, a distal end 137 and a proximal end 138.

The base portion 158 of the backing layer 130 is positioned such that its second surface 132 is adjacent to the top surface

110 of the electrode 107. The base portion 158 of the backing layer 130 is sized and positioned so that the distal end 137 and proximal end 138 of the base portion 158 of the backing layer 130 overlay the second pair of sides 109 of the main body 217 of the electrode 107. The distal end 137 and proximal end 138 of the are also substantially parallel and of substantially the same size as the second pair of sides 109 of the electrode 107.

The integrated fin tab 180 of the backing layer 130 is formed from the same piece of material as the base portion 158 of the backing layer 130. The integrated fin tab 180 is formed on the first surface 131 of the base portion 158 of the backing layer 130.

The integrated fin tab 180 comprises a proximal edge 183, a distal edge 184, a top 185 and a bottom 186. The bottom 186 of the integrated fin tab 180 is joined to the first surface 131 of the base portion 158 of the backing layer 130. The proximal edge 183 and the distal edge 184 of the integrated fin tab 180 extend from, and substantially perpendicular to the first surface 131 of the base portion 158 of the backing layer 130. The proximal edge 183 and distal edge 184 of the integrated fin tab 180 are parallel with each other. The integrated fin tab 180 is positioned so that its proximal edge 183 is substantially flush with the proximal end 138 of the base portion 158 of the backing layer 130.

The backing layer 130 is composed of polyurethane. In an alternative embodiment, the backing layer 130 is composed of silicone. In another alternative embodiment, the backing layer 130 is composed of any polymeric material.

5 The molded cover 220 envelops and holds together the components of the lead electrode assembly 100. The molded cover 220 also provides rigidity to the lead electrode assembly 100. The molded cover 220 envelops the lead fastener 146 and the backing layer 130. The fin 120 is formed when the molded cover 220 covers the fin tab 180. The thickness of the resulting fin 120 is approximately 2 mm. In alternate embodiments, the thickness of the fin 120 is between approximately 1 mm and approximately 3 mm.

10 The appendage height of the fin 120 in this embodiment is approximately 5 mm. In alternative embodiments, the appendage heights range between approximately 1 mm and approximately 10 mm. The appendage length of the fin 120 in this embodiment is approximately 1 cm. In alternative embodiments, appendage lengths range between approximately 2 mm and approximately 6 cm.

20 In one embodiment, the appendage length of the fin 120 is such that the fin is as long as the backing layer. In one embodiment, the appendage length of the fin 120 is such that the fin is as long as the electrode 107. In one embodiment, the



appendage length of the fin 120 is such that the fin is as long as the molded cover 220.

The molded cover 220 also partially covers the bottom surface 115 of the electrode 107. In this way, the molded cover 5 220 attaches the backing layer 130 to the electrode 107.

The molded cover 220 in this embodiment is made of silicone. In an alternate embodiment, the molded cover 220 is made of any polymeric material. Stitching 360 holds the molded cover 220, the electrode 107 and the backing layer 130 together.

In one embodiment, the fin 120 is reinforced with a layer of Dacron® polymer mesh positioned between the molded cover 220 and the integrated fin tab 180. In another embodiment, the Dacron® polymer mesh is attached only to the molded cover 220. In other embodiments, the fin 120 is similarly reinforced with a layer of any polymeric material.

As shown in FIG. 17(b), the fin 120 of the embodiment illustrated in FIG. 17(a) can alternately have a sloped shape. The sloped shape can reduce the resistance offered by the tissue of the patient as it slides against the fin 120 during the 20 insertion of the lead electrode assembly 100 into the patient. The slope-shaped fin 120 is constructed so that the proximal edge 183 and distal edge 184 of the integrated fin tab 180 are not parallel with each other. Instead, proximal edge 183 of the integrated fin tab 180 can be curved so that the proximal edge

183 of the integrated fin tab 180 is closer to the proximal edge 184 at the top 185 of the integrated fin tab 180, than at the bottom 186 of the integrated fin tab 180. In alternate embodiments, the proximal edge 183 of the integrated fin tab 180 is not curved. Instead, the proximal edge 183 of the integrated fin tab 180 is straight, and forms an acute angle with the first surface 131 of the backing layer 130. In one alternate embodiment, the proximal edge 183 of the integrated fin tab 180 forms a 45 degree angle with the first surface 131 of the backing layer 130. In alternate embodiments, the distal edge 184 of the integrated fin tab 180 is curved. In alternate embodiments, the distal edge 184 of the integrated fin tab 180 is straight and shaped so that it forms an acute angle with the first surface 131 of the backing layer 130.

FIG. 17(c) illustrates a front plan view of the lead electrode assembly 100 seen in FIG. 17(a). The base portion 158 of the backing layer 130 further comprises a first side 133 and second side 134. The first side 133 and second side 134 of the base portion 158 of the backing layer 130 are substantially parallel. In an alternate embodiment, the first side 133 and second side 134 of the backing layer 130 are not parallel. The base portion 158 of the backing layer 130 is sized so that it is substantially the same size and shape as the main body 217 of the electrode 107.

The integrated fin tab 180 of the backing layer 130 is planar, comprising a first face 181 and a second face 182. The first face 181 and second face 182 of the fin tab 180 are substantially parallel with each other and with the first side 133 and second side 134 of the backing layer 130. The first face 181 and second face 182 of the fin tab 180 extend from, and substantially perpendicular to the first surface 131 of the backing layer 130. In another embodiment, the first face 181 and second face 182 of the fin tab 180 extend from the first surface 131 of the backing layer 130 at angles other than a right angle.

In an alternate embodiment, the first face 181 and a second face 182 of the integrated fin tab 180 of the backing layer 130 are not substantially parallel to each other. Instead, they are angled, such that they are closer together at the top 185 than they are at the bottom 186 of the integrated fin tab 180. This shape can reduce the resistance offered by the tissue of the patient as it slides against the fin 120 during the insertion of the lead electrode assembly 100 into the patient.

In another embodiment, the first face 181 and a second face 182 of the integrated fin tab 180 of the backing layer 130 are angled, such that they are further apart at the top 185 than they are at the bottom 186 of the integrated fin tab 180. This

shape can make the fin 120 easier to grip with a tool, such as a hemostat.

5 The fin tab 180 extends from the backing layer 130 at a position centered between the first side 133 and the second side 134 of the backing layer 130. In an alternate embodiment, the fin tab 180 is not centered between the first side 133 and the second side 134 of the backing layer 130.

10 An eyelet 301 is formed in the fin 120 of this embodiment. The eyelet can be used to facilitate the capture of the lead electrode assembly by a tool. The eyelet is formed as a hole 225 through the molded cover 220 and between the faces 181 and 182 of fin tab 180. In an alternate embodiment, no eyelet is formed in the fin 120.

15 The bottom surface 115 of the electrode 107 comprises a periphery 213 and a center 211. The molded cover 220 forms a skirt 222 around the periphery 213 of the bottom surface 115 of the electrode 107. The skirt 222 of the molded cover 220 covers the periphery 213 of the bottom surface 115 of the electrode 107.

20 The skirt 222 of the molded cover 220 can act to focus cardioversion/defibrillation energy emitted from the electrode 107 of the lead electrode assembly 100 toward the heart of the patient. Because the thorax of a patient is surrounded by a layer of fat that is somewhat conductive, the cardioversion

/defibrillation energy may tend to arc through this layer to reach the active surface 15 of the canister 11 (seen in FIG. 1) without passing through the patient's heart. The skirt 222 of the lead electrode assembly 100 acts to minimize the loss of 5 cardioversion /defibrillation energy to surrounding body tissues, or from being diverted away from the patient's heart.

The center 211 of the bottom surface 115 of the electrode 107 is not covered by the molded cover 220 and is left exposed. The width of the periphery 213 of the bottom surface 115 of the electrode 107 covered by the molded cover 220 is approximately .125 cm.

The area of the exposed center 211 of the bottom surface 115 of the electrode 107 is approximately 500 square mm. In alternative embodiments, the length of the first pair of sides 108 and the second pair of sides 109 of the electrode 107 vary, such that the area of the center 211 of the bottom surface 115 of the electrode has a surface area between approximately 100 sq. mm. and approximately 2000 sq. mm.

FIG. 17(d) illustrates an exploded top view of the lead 20 fastener 146 of the embodiments illustrated in FIGS. 17(a)-17(c). The lead fastener connects the proximal end 102 of the lead 21 and the distal end 103 of the electrode 107.

In this embodiment, the lead fastener 146 comprises a first crimping tube 200, a crimping pin 202 and a second crimping tube

201. The crimping pin 202 comprises a first side 203 and a second side 204.

The crimping tube 200 crimps the filars 147 of the lead 21 (here, only one representative filar 147 is shown) to the first side 203 of crimping pin 202. The mandrel 219 of the electrode 107 is then wrapped around the second side 204 of the crimping pin 202. Crimping tube 201 crimps the mandrel 219 to the second side 204 of the crimping pin 202.

10 15 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 155 160 165 170 175 180 185 190 195 200 205 210 215 220 225 230 235 240 245 250 255 260 265 270 275 280 285 290 295 300 305 310 315 320 325 330 335 340 345 350 355 360 365 370 375 380 385 390 395 400 405 410 415 420 425 430 435 440 445 450 455 460 465 470 475 480 485 490 495 500 505 510 515 520 525 530 535 540 545 550 555 560 565 570 575 580 585 590 595 600 605 610 615 620 625 630 635 640 645 650 655 660 665 670 675 680 685 690 695 700 705 710 715 720 725 730 735 740 745 750 755 760 765 770 775 780 785 790 795 800 805 810 815 820 825 830 835 840 845 850 855 860 865 870 875 880 885 890 895 900 905 910 915 920 925 930 935 940 945 950 955 960 965 970 975 980 985 990 995 1000

The first crimping tube 200, the second crimping tube 201 and the crimping pin 202 are each made of platinum iridium. In an alternative embodiment, the first crimping tube 200, the second crimping tube 201 and the crimping pin 202 are each made of a metal selected from the group consisting essentially of titanium, nickel alloys, stainless steel alloys, platinum, platinum iridium, and mixtures thereof. In other embodiments, the first crimping tube 200, the second crimping tube 201 and the crimping pin 202 each comprise any conductive material.

20 The electrode 107 in this embodiment comprises a sheet of metallic mesh 206 prepared by the process described with reference to FIG. 14. The electrode 107 has a width measured parallel to the second pair of sides 109 of the electrode 107. The width of the mandrel neck 218 of the electrode 107 is approximately 3 mm wide. The width of the mandrel of the electrode 107 is approximately 5 mm wide.

The first pair of sides 108 of the electrode 107 are approximately 5 cm in length. The second pair of sides 109 of the electrode 107 are approximately 1.9 cm in length. In alternative embodiments, the length of the first pair of sides 5 108 and the second pair of sides 109 of the electrode 107 range independently from approximately 1 cm to approximately 5 cm.

The electrode 107 of this embodiment further comprises four corners 112. The corners 112 of the electrode 107 are rounded. In an alternate embodiment, the corners 112 of the electrode 107 are not rounded.

FIGS. 17(e)-17(g) illustrate the size and position of the fin 120 on the molded cover of the lead electrode assembly 100.

FIGS. 18(a)-18(c) illustrate an alternative embodiment of the lead electrode assembly 100. This embodiment is substantially similar to the embodiments illustrated in FIGS. 17(a)-17(g). In this embodiment, however, the appendage height of the fin 120 is approximately 1 cm. The appendage length of the fin 120 in this embodiment is approximately 3.5 cm.

As shown in FIG. 18(a), stitching 302 is placed through the 20 molded cover 220 and the fin 120 to prevent the molded cover 220 from sliding off the fin tab 180 when the molded cover 220 is subjected to a force directed away from the electrode 107.

As shown in FIG. 18(c), the fin 120 (phantom view) extends approximately two thirds of the length of the electrode 107.

FIG. 19 illustrates an alternative embodiment of the lead electrode assembly 100. This embodiment is substantially similar to the embodiments illustrated in FIGS. 17(a)-17(g). In this embodiment, however, the backing layer 130 (not shown) inside the molded cover 220 is curved. This results in an electrode 107 that has a curvature of radius  $r$ , such that the bottom surface 115 of the electrode 107 is concave.

Because a curved electrode 107 may more closely approximate the curvature of the patient's ribs, this curvature may have the effect of making the lead electrode assembly 100 more comfortable for the patient. In one embodiment, the radius  $r$  of the curvature varies throughout the electrode 107 such that it is intentionally shaped to approximate the shape of the ribs. Lead electrode assemblies 100 can be custom manufactured with an electrode 107 with a curvature  $r$  that matches the curvature of the intended patient's ribcage in the vicinity of the ribcage adjacent to which the electrode 107 is to be positioned.

In an alternative embodiment, lead electrode assemblies 100 are manufactured with an electrode 107 with a radius  $r$  that matches the curvature of the ribcage of a statistically significant number of people.

In another embodiment, lead electrode assemblies 100 with electrodes 107 of varying curvatures can be manufactured to



allow an electrode radius  $r$  to be selected for implantation based on the size of the patient. Smaller radii can be used for children and for smaller adult patients. Larger radii can be used for larger patients. The radius  $r$  of the curvature can range from approximately 5 cm to approximately 35 cm depending on the size of the patient.

In an alternative embodiment, the electrode 107 of the lead electrode assembly 100 is flexible, such that it can be bent to conform to the curvature of the intended patient's rib cage at the time of implantation.

FIGS. 20(a)-20(c) illustrate an alternative embodiment of the lead electrode assembly 100. This embodiment is substantially similar to the embodiments illustrated in FIGS. 17(a)-17(g). In this embodiment, however, the backing layer 130 lacks an integrated fin tab 180 mounted on the first surface 131 of the backing layer 130. Moreover, this embodiment further comprises a backing layer 400 having a fin tab 405.

FIGS. 20(a) and 20(b) illustrate only the backing layer 400, the fin tab 405 and the electrode 107 of this embodiment as they are positioned relative to each other in the complete embodiment. Other components of the embodiment are not shown. FIG. 20(c) shows the embodiment in a complete form.

FIG. 20(a) illustrates a top plan view of the backing layer 400 and the electrode 107. The backing layer 400 is positioned

over the electrode 107. The electrode 107 of this embodiment is substantially similar to the electrode 107 of the embodiment illustrated in FIG. 17(d). In the complete embodiment, the mandrel 219 of the electrode 107 is joined to the lead 21 (not shown) by a lead fastener 146 (not shown) as shown in FIG. 17(a).

The backing layer 400 is a flat, planar member comprising a distal end 137 and a proximal end 138. The backing layer 400 further comprises a first side 133, a second side 134, a first surface 131, and a second surface 132 (not shown). The backing layer 400 further comprises a width, W, measured as the distance between the first side 133 and the second side 134.

The backing layer 400 includes a fin tab 405 that is formed from the same piece of material as the backing layer 400. The first side 133 of the backing layer 400 lies over one of the first pair of sides 108 of the electrode 107 except over a fin tab region 407. In the fin tab region 407, the backing layer 400 is wider than the electrode 107. In the fin tab region 407, the first side 133 forms a fin tab 405 that protrudes from part of the first side 133 of the backing layer 400 outside the fin tab region 407. The fin tab 405 extends from the first side 133 of the backing layer 400 in an orientation substantially parallel to the top surface 110 of the electrode 107, beyond the first side 108 (phantom view) of the electrode 107.

The fin tab 405 comprises a first face 410 and a second face 411 (not shown). The first face 410 of the fin tab 405 is an extension of the first surface 131 of the backing layer 400. The second face 411 of the fin tab 405 is an extension of the second surface 132 of the backing layer 400.

Aside from the fin tab 405, the backing layer 405 is formed so that it is of substantially the same size and shape as the main body 217 of the electrode 107.

The backing layer 400, including the fin tab 405, is composed of polyurethane. In an alternate embodiments the backing layer 400 and fin tab 405 are composed of any polymeric material.

FIG 20(b) is a side plan view of the backing layer 400 and the electrode 107. The backing layer 400 is positioned over the electrode 107 such that the second surface 132 of the backing layer 400 is placed adjacent to the top surface 110 of the electrode 107.

FIG. 20(c) illustrates a bottom plan view of the complete embodiment, in which the backing layer 400 (not shown), the lead fastener 146 (not shown) and the fin tab 405 (phantom view) are coated with a molded cover 220. When the molded cover 220 is applied over the backing layer 400, a fin 424 is formed over the fin tab 405 (phantom view). The fin 424 comprises a proximal end 404 and a distal end 403.

In one embodiment, the fin 424 is reinforced with a layer of Dacron® polymer mesh positioned between the molded cover 220 and the fin tab 405. In another embodiment, the Dacron® polymer mesh is attached only to the molded cover 220. In other 5 embodiments, the fin 424 is similarly reinforced with a layer of any polymeric material.

The appendage height,  $h_{\text{Appendage}}$ , of the fin 424 of this embodiment is approximately 5 mm. In alternative embodiments, the appendage heights range between approximately 1 mm and approximately 10 mm. The appendage length,  $L_{\text{Appendage}}$ , of the fin 424 of this embodiment is measured between the proximal end 404 and the distal end 403 of the fin 424.  $L_{\text{Appendage}}$  is measured where the fin 424 joins the rest of the lead electrode assembly 100. In this embodiment, the appendage length is approximately 1 cm. In alternative embodiments, the appendage lengths range between approximately 2 mm and approximately 6 cm. In one embodiment, the appendage length of the fin 424 is such that the fin 424 runs the length of the electrode 107. In one embodiment, the appendage length of the fin 424 is such that the 20 fin 424 runs the length of the backing layer 130 (not shown). In one embodiment, the appendage length of the fin 424 is such that the fin 424 runs the length of the molded cover 220.

FIG. 20(d) illustrates a bottom plan view of an alternate embodiment of the lead electrode assembly 100. This embodiment

is substantially similar to the lead electrode assembly 100 illustrated in FIGS. 20(a)-20(c). In this embodiment, however, proximal end 404 of the fin 424 is sloped. The slope shape of the fin 424 is formed by the shape of the fin tab 405 (phantom view) inside the fin 424. The backing layer 400 gradually widens in the fin tab region 407 (not shown) with distance from the proximal end 138 (not shown) to the distal end 137 (not shown) of the backing layer 130 (not shown) until the appendage height is reached. The proximal end 404 of the fin 424 is straight and forms an acute angle with the first side 133 of the base portion 158 of the backing layer 130 (not shown). In an alternate embodiment, the proximal end 404 of the fin 424 forms a 45 degree angle with the first side 133 of the base portion 158 of the backing layer 130 (not shown). In another embodiment, the proximal end 404 of the fin 424 is curved slope.

In alternate embodiments, the distal end 403 of the fin 424 is straight and shaped so that it forms an acute angle with the first side 133 of the base portion 158 of the backing layer 130 (not shown). In alternate embodiments, the distal end 403 of the fin 424 is curved.

FIGS. 21(a)-21(c) illustrate an alternative embodiment of the lead electrode assembly 100. This embodiment is substantially similar to the embodiment illustrated in FIGS.

15(a)-15(b). The integrated fin 120 is absent, however, from the backing layer 130.

The lead electrode assembly 100 of this embodiment further comprises a cylindrical rod 500 having a loop 515 formed therein. The loop 515 comprises the appendage 118 of this embodiment. The loop 515 is a member attached to the electrode 107 that can be gripped and used to precisely locate the electrode 107 during its surgical implantation within the patient.

FIG. 21(a) illustrates a side plan view of the embodiment. The cylindrical rod 500 comprises a first straight portion 510, a second straight portion 512 and a portion formed into a loop 515. The first straight portion 510 is separated from the second straight portion 512 by the loop 515.

The rod 500 is made of platinum iridium. In an alternative embodiment, the rod 500 is made of titanium or platinum.

The first straight portion 510 and second straight portion 512 are spot welded to the top surface 110 of the electrode 107. The loop 515 in the rod 500 extends away from the top surface 110 of the electrode 107.

The backing layer 130 is similar to the backing layer 130 illustrated in FIGS. 15(a)-15(b). The backing layer 130 is disposed over the electrode 107. The first straight portion 510 and second straight portion 512 of the rod 500 are positioned

between the second surface 132 of the backing layer 130 and the top surface 110 of the electrode 107.

FIG. 21(b) illustrates a cross-sectional rear plan view of the embodiment of the lead electrode assembly shown in FIG.

21(a). The first straight portion 510 and second straight portion 512 are positioned such that they are parallel to the first pair of sides 108 of the electrode 107. The first straight portion 510 and second straight portion 512 are both centered between the first pair of sides 108 of the electrode 107. In an alternative embodiment, the first straight portion 510 and second straight portion 512 are not parallel to and centered between the first pair of sides 108 of the electrode 107.

FIG. 21(c) illustrates a top plan view of the embodiment of the lead electrode assembly shown in FIG. 21(a). An aperture 517 is formed in the backing layer 130. The aperture 517 in the backing layer is positioned such that the loop 515 extends through and beyond the aperture 517 in a direction away from the top surface 110 of the electrode 107. The backing layer 130 is attached to the electrode 107 with stitching 139.

FIGS. 22(a)-22(d) illustrate an alternative embodiment of the lead electrode assembly 100. This embodiment is substantially similar to the embodiment illustrated in FIGS. 15(a)-15(b). This embodiment comprises a backing layer 610,

however, that lacks the integrated fin 120 illustrated in FIGS. 15(a)-15(b).

FIG. 22(a) illustrates a top plan view of the backing layer 610 of this embodiment prior to its attachment to the rest of the lead electrode assembly 100. The backing layer 610 is cut in a pattern as shown. The backing layer comprises a first surface 131, a second surface 132 (not shown), a distal end 137, a proximal end 138, a first side 133, a second side 134 and an indented fin-forming region 620. The indented fin-forming region 620 comprises a first edge 690 and a second edge 691.

The backing layer 610 is formed so that the first side 133 and the second side 134 are substantially parallel and of substantially the same size as the first pair of sides 108 of the electrode 107. The proximal end 138 is formed so that it is substantially perpendicular to the first side 133 and the second side 134 of the backing layer 610. The proximal end 138 is longer than the second pair of sides 109 of the electrode 107 by a length A. The backing layer 610 has a varying width C measured from its distal end 137 to its proximal end 138 along a line parallel to its first side 133.

The backing layer is divided into three sections. A first backing section 693, a second backing section 692 and an indented fin-forming region 620 of length A. The length of the fin-forming region 620, A, is approximately 10 mm. In other



embodiments, the length of the fin-forming region 620, A, ranges between approximately 2 mm and approximately 20 mm.

The area within the indented fin-forming region 620 is equally divided into a first fin area 612 and a second fin area 5 615. The dividing line 617 between the first fin area 612 and the second fin area 615 is substantially parallel to the first side 133.

10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200 210 220 230 240 250 260 270 280 290 300 310 320 330 340 350 360 370 380 390 400 410 420 430 440 450 460 470 480 490 500 510 520 530 540 550 560 570 580 590 600 610 620 630 640 650 660 670 680 690 700 710 720 730 740 750 760 770 780 790 800 810 820 830 840 850 860 870 880 890 900 910 920 930 940 950 960 970 980 990 1000 1010 1020 1030 1040 1050 1060 1070 1080 1090 1100 1110 1120 1130 1140 1150 1160 1170 1180 1190 1200 1210 1220 1230 1240 1250 1260 1270 1280 1290 1300 1310 1320 1330 1340 1350 1360 1370 1380 1390 1400 1410 1420 1430 1440 1450 1460 1470 1480 1490 1500 1510 1520 1530 1540 1550 1560 1570 1580 1590 1600 1610 1620 1630 1640 1650 1660 1670 1680 1690 1700 1710 1720 1730 1740 1750 1760 1770 1780 1790 1800 1810 1820 1830 1840 1850 1860 1870 1880 1890 1900 1910 1920 1930 1940 1950 1960 1970 1980 1990 2000 2010 2020 2030 2040 2050 2060 2070 2080 2090 2100 2110 2120 2130 2140 2150 2160 2170 2180 2190 2200 2210 2220 2230 2240 2250 2260 2270 2280 2290 2300 2310 2320 2330 2340 2350 2360 2370 2380 2390 2400 2410 2420 2430 2440 2450 2460 2470 2480 2490 2500 2510 2520 2530 2540 2550 2560 2570 2580 2590 2600 2610 2620 2630 2640 2650 2660 2670 2680 2690 2700 2710 2720 2730 2740 2750 2760 2770 2780 2790 2800 2810 2820 2830 2840 2850 2860 2870 2880 2890 2900 2910 2920 2930 2940 2950 2960 2970 2980 2990 3000 3010 3020 3030 3040 3050 3060 3070 3080 3090 3100 3110 3120 3130 3140 3150 3160 3170 3180 3190 3200 3210 3220 3230 3240 3250 3260 3270 3280 3290 3300 3310 3320 3330 3340 3350 3360 3370 3380 3390 3400 3410 3420 3430 3440 3450 3460 3470 3480 3490 3500 3510 3520 3530 3540 3550 3560 3570 3580 3590 3600 3610 3620 3630 3640 3650 3660 3670 3680 3690 3700 3710 3720 3730 3740 3750 3760 3770 3780 3790 3800 3810 3820 3830 3840 3850 3860 3870 3880 3890 3900 3910 3920 3930 3940 3950 3960 3970 3980 3990 4000 4010 4020 4030 4040 4050 4060 4070 4080 4090 4100 4110 4120 4130 4140 4150 4160 4170 4180 4190 4200 4210 4220 4230 4240 4250 4260 4270 4280 4290 4300 4310 4320 4330 4340 4350 4360 4370 4380 4390 4400 4410 4420 4430 4440 4450 4460 4470 4480 4490 4500 4510 4520 4530 4540 4550 4560 4570 4580 4590 4600 4610 4620 4630 4640 4650 4660 4670 4680 4690 4700 4710 4720 4730 4740 4750 4760 4770 4780 4790 4800 4810 4820 4830 4840 4850 4860 4870 4880 4890 4900 4910 4920 4930 4940 4950 4960 4970 4980 4990 5000 5010 5020 5030 5040 5050 5060 5070 5080 5090 5100 5110 5120 5130 5140 5150 5160 5170 5180 5190 5200 5210 5220 5230 5240 5250 5260 5270 5280 5290 5300 5310 5320 5330 5340 5350 5360 5370 5380 5390 5400 5410 5420 5430 5440 5450 5460 5470 5480 5490 5500 5510 5520 5530 5540 5550 5560 5570 5580 5590 5600 5610 5620 5630 5640 5650 5660 5670 5680 5690 5700 5710 5720 5730 5740 5750 5760 5770 5780 5790 5800 5810 5820 5830 5840 5850 5860 5870 5880 5890 5900 5910 5920 5930 5940 5950 5960 5970 5980 5990 6000 6010 6020 6030 6040 6050 6060 6070 6080 6090 6100 6110 6120 6130 6140 6150 6160 6170 6180 6190 6200 6210 6220 6230 6240 6250 6260 6270 6280 6290 6300 6310 6320 6330 6340 6350 6360 6370 6380 6390 6400 6410 6420 6430 6440 6450 6460 6470 6480 6490 6500 6510 6520 6530 6540 6550 6560 6570 6580 6590 6600 6610 6620 6630 6640 6650 6660 6670 6680 6690 6700 6710 6720 6730 6740 6750 6760 6770 6780 6790 6800 6810 6820 6830 6840 6850 6860 6870 6880 6890 6900 6910 6920 6930 6940 6950 6960 6970 6980 6990 7000 7010 7020 7030 7040 7050 7060 7070 7080 7090 7100 7110 7120 7130 7140 7150 7160 7170 7180 7190 7200 7210 7220 7230 7240 7250 7260 7270 7280 7290 7300 7310 7320 7330 7340 7350 7360 7370 7380 7390 7400 7410 7420 7430 7440 7450 7460 7470 7480 7490 7500 7510 7520 7530 7540 7550 7560 7570 7580 7590 7600 7610 7620 7630 7640 7650 7660 7670 7680 7690 7700 7710 7720 7730 7740 7750 7760 7770 7780 7790 7800 7810 7820 7830 7840 7850 7860 7870 7880 7890 7900 7910 7920 7930 7940 7950 7960 7970 7980 7990 8000 8010 8020 8030 8040 8050 8060 8070 8080 8090 8100 8110 8120 8130 8140 8150 8160 8170 8180 8190 8200 8210 8220 8230 8240 8250 8260 8270 8280 8290 8300 8310 8320 8330 8340 8350 8360 8370 8380 8390 8400 8410 8420 8430 8440 8450 8460 8470 8480 8490 8500 8510 8520 8530 8540 8550 8560 8570 8580 8590 8600 8610 8620 8630 8640 8650 8660 8670 8680 8690 8700 8710 8720 8730 8740 8750 8760 8770 8780 8790 8800 8810 8820 8830 8840 8850 8860 8870 8880 8890 8900 8910 8920 8930 8940 8950 8960 8970 8980 8990 9000 9010 9020 9030 9040 9050 9060 9070 9080 9090 9100 9110 9120 9130 9140 9150 9160 9170 9180 9190 9200 9210 9220 9230 9240 9250 9260 9270 9280 9290 9300 9310 9320 9330 9340 9350 9360 9370 9380 9390 9400 9410 9420 9430 9440 9450 9460 9470 9480 9490 9500 9510 9520 9530 9540 9550 9560 9570 9580 9590 9600 9610 9620 9630 9640 9650 9660 9670 9680 9690 9700 9710 9720 9730 9740 9750 9760 9770 9780 9790 9800 9810 9820 9830 9840 9850 9860 9870 9880 9890 9900 9910 9920 9930 9940 9950 9960 9970 9980 9990 10000 10010 10020 10030 10040 10050 10060 10070 10080 10090 10100 10110 10120 10130 10140 10150 10160 10170 10180 10190 10200 10210 10220 10230 10240 10250 10260 10270 10280 10290 10300 10310 10320 10330 10340 10350 10360 10370 10380 10390 10400 10410 10420 10430 10440 10450 10460 10470 10480 10490 10500 10510 10520 10530 10540 10550 10560 10570 10580 10590 10600 10610 10620 10630 10640 10650 10660 10670 10680 10690 10700 10710 10720 10730 10740 10750 10760 10770 10780 10790 10800 10810 10820 10830 10840 10850 10860 10870 10880 10890 10900 10910 10920 10930 10940 10950 10960 10970 10980 10990 11000 11010 11020 11030 11040 11050 11060 11070 11080 11090 11100 11110 11120 11130 11140 11150 11160 11170 11180 11190 11200 11210 11220 11230 11240 11250 11260 11270 11280 11290 11300 11310 11320 11330 11340 11350 11360 11370 11380 11390 11400 11410 11420 11430 11440 11450 11460 11470 11480 11490 11500 11510 11520 11530 11540 11550 11560 11570 11580 11590 11600 11610 11620 11630 11640 11650 11660 11670 11680 11690 11700 11710 11720 11730 11740 11750 11760 11770 11780 11790 11800 11810 11820 11830 11840 11850 11860 11870 11880 11890 11900 11910 11920 11930 11940 11950 11960 11970 11980 11990 12000 12010 12020 12030 12040 12050 12060 12070 12080 12090 12100 12110 12120 12130 12140 12150 12160 12170 12180 12190 12200 12210 12220 12230 12240 12250 12260 12270 12280 12290 12300 12310 12320 12330 12340 12350 12360 12370 12380 12390 12400 12410 12420 12430 12440 12450 12460 12470 12480 12490 12500 12510 12520 12530 12540 12550 12560 12570 12580 12590 12600 12610 12620 12630 12640 12650 12660 12670 12680 12690 12700 12710 12720 12730 12740 12750 12760 12770 12780 12790 12800 12810 12820 12830 12840 12850 12860 12870 12880 12890 12900 12910 12920 12930 12940 12950 12960 12970 12980 12990 13000 13010 13020 13030 13040 13050 13060 13070 13080 13090 13100 13110 13120 13130 13140 13150 13160 13170 13180 13190 13200 13210 13220 13230 13240 13250 13260 13270 13280 13290 13300 13310 13320 13330 13340 13350 13360 13370 13380 13390 13400 13410 13420 13430 13440 13450 13460 13470 13480 13490 13500 13510 13520 13530 13540 13550 13560 13570 13580 13590 13600 13610 13620 13630 13640 13650 13660 13670 13680 13690 13700 13710 13720 13730 13740 13750 13760 13770 13780 13790 13800 13810 13820 13830 13840 13850 13860 13870 13880 13890 13900 13910 13920 13930 13940 13950 13960 13970 13980 13990 14000 14010 14020 14030 14040 14050 14060 14070 14080 14090 14100 14110 14120 14130 14140 14150 14160 14170 14180 14190 14200 14210 14220 14230 14240 14250 14260 14270 14280 14290 14300 14310 14320 14330 14340 14350 14360 14370 14380 14390 14400 14410 14420 14430 14440 14450 14460 14470 14480 14490 14500 14510 14520 14530 14540 14550 14560 14570 14580 14590 14600 14610 14620 14630 14640 14650 14660 14670 14680 14690 14700 14710 14720 14730 14740 14750 14760 14770 14780 14790 14800 14810 14820 14830 14840 14850 14860 14870 14880 14890 14900 14910 14920 14930 14940 14950 14960 14970 14980 14990 15000 15010 15020 15030 15040 15050 15060 15070 15080 15090 15100 15110 15120 15130 15140 15150 15160 15170 15180 15190 15200 15210 15220 15230 15240 15250 15260 15270 15280 15290 15300 15310 15320 15330 15340 15350 15360 15370 15380 15390 15400 15410 15420 15430 15440 15450 15460 15470 15480 15490 15500 15510 15520 15530 15540 15550 15560 15570 15580 15590 15600 15610 15620 15630 15640 15650 15660 15670 15680 15690 15700 15710 15720 15730 15740 15750 15760 15770 15780 15790 15800 15810 15820 15830 15840 15850 15860 15870 15880 15890 15900 15910 15920 15930 15940 15950 15960 15970 15980 15990 16000 16010 16020 16030 16040 16050 16060 16070 16080 16090 16100 16110 16120 16130 16140 16150 16160 16170 16180 16190 16200 16210 16220 16230 16240 16250 16260 16270 16280 16290 16300 16310 16320 16330 16340 16350 16360 16370 16380 16390 16400 16410 16420 16430 16440 16450 16460 16470 16480 16490 16500 16510 16520 16530 16540 16550 16560 16570 16580 16590 16600 16610 16620 16630 16640 16650 16660 16670 16680 16690 16700 16710 16720 16730 16740 16750 16760 16770 16780 16790 16800 16810 16820 16830 16840 16850 16860 16870 16880 16890 16900 16910 16920 16930 16940 16950 16960 16970 16980 16990 17000 17010 17020 17030 17040 17050 17060 17070 17080 17090 17100 17110 17120 17130 17140 17150 17160 17170 17180 17190 17200 17210 17220 17230 17240 17250 17260 17270 17280 17290 17300 17310 17320 17330 17340 17350 17360 17370 17380 17390 17400 17410 17420 17430 17440 17450 17460 17470 17480 17490 17500 17510 17520 17530 17540 17550 17560 17570 17580 17590 17600 17610 17620 17630 17640 17650 17660 17670 17680 17690 17700 17710 17720 17730 17740 17750 17760 17770 17780 17790 17800 17810 17820 17830 17840 17850 17860 17870 17880 17890 17900 17910 17920 17930 17940 17950 17960 17970 17980 17990 18000 18010 18020 18030 18040 18050 18060 18070 18080 18090 18100 18110 18120 18130 18140 18150 18160 18170 18180 18190 18200 18210 18220 18230 18240 18250 18260 18270 18280 18290 18300 18310 18320 18330 18340 18350 18360 18370 18380 18390 18400 18410 18420 18430 18440 18450 18460 18470 18480 18490 18500 18510 18520 18530 18540 18550 18560 18570 18580 18590 18600 18610 18620 18630 18640 18650 18660 18670 18680 18690 18700 18710 18720 18730 18740 18750 18760 18770 18780 18790 18800 18810 18820 18830 18840 18850 18860 18870 18880 18890 18900 18910 18920 18930 18940 18950 18960 18970 18980 18990 19000 19010 19020 19030 19040 19050 19060 19070 19080 19090 19100 19110 19120 19130 19140 19150 19160 19170 19180 19190 19200 19210 19220 19230 19240 19250 19260 19270 19280 19290 19300 19310 19320 19330 19340 19350 19360 19370 19380 19390 19400 19410 19420 19430 19440 19450 19460 19470 19480 19490 19500 19510 19520 19530 19540 19550 19560 19570 19580 19590 19600 19610 19620 19630 19640 19650 19660 19670 19680 19690 19700 19710 19720 19730 19740 19750 19760 19770 19780 19790 19800 19810 19820 19830 19840 19850 19860 19870 19880 19890 19900 19910 19920 19930 19940 19950 19960 19970 19980 19990 20000 20010 20020 20030 20040 20050 20060 20070 20080 20090 20100 20110 20120 20130 20140 20150 20160 20170 20180 20190 20200 20210 20220 20230 20240 20250 20260 20270 20280 20290 20300 20310 20320 20330 20340 20350 20360 20370 20380 20390 20400 20410 20420 20430 20440 20450 20460 20470 20480 20490 20500 20510 20520 20530 20540 20550 20560 20570 20580 20590 20600 20610 20620 20630 20640 20650 20660 20670 20680 20690 20700 20710 20720 20730 20740 20750 20760 20770 20780 20790 20800 20810 20820 20830 20840 20850 20860 20870 20880 20890 20900 20910 20920 20930 20940 20950 20960 20970 20980 20990 21000 21010 21020 21030 21040 21050 21060 21070 21080 21090 21100 21110 21120 21130 21140 21150 21160 21170 21180 21190 21200 21210 21220 21230 21240 21250 21260 21270 21280 21290 21300 21310 21320 21330 21340 21350 21360 21370 21380 21390 21400 21410 21420 21430 21440 21450 21460 21470 21480 21490 21500 21510 21520 21530 21540 21550 21560 21570 21580 21590 21600 21610 21620 21630 21640 21650 21660 21670 21680 21690 21700 21710 21720 21730 21740 21750 21760 21770 21780 21790 21800 21810 21820 21830 21840 21850 21860 21870 21880 21890 21900 21910 21920 21930 21940 21950 21960 21970 21980 21990 22000 22010 22020 22030 22040 22050 22060 22070 220

layer 130. A second notch 136(b) is formed on the distal end 137 the second edge 691 of the fin-forming region 620 of the backing layer 130.

The backing layer 610 in this embodiment is formed of flexible silicone. In alternative embodiments the backing layer 610 is formed of any bio-compatible, flexible polymeric material.

FIG. 22(b) illustrates a top plan view of the lead electrode assembly 100 of this embodiment. The backing layer 610 is attached to the electrode 107, so that the first edge 690 and a second edge 691 of the fin-forming region 620 of the backing layer 610 meet. This causes the backing layer 610 in the first fin area 612 and the second fin area 615 to fold together to form a fin 120.

The first notch 136(a) and second notch 136(b) formed on the distal end 137 the first edge 690 and second edge 691 of the fin-forming region 620 of the backing layer 130 meet to form a notch 136 on the distal end 137 of the backing layer, through which the lead fastener 146 rises. Stitching 660 holds the backing layer to the electrode 107.

FIG. 22(c) illustrates a side plan view of the lead electrode assembly 100 of this embodiment. Stitching 660 holds the first fin area 612 and a second fin area 615 of the backing layer 610 together to form the fin 120.

FIG. 22(d) illustrates a front plan view of the lead electrode assembly 100 of this embodiment. In one embodiment, the fin 120 is reinforced with a layer of Dacron® polymer mesh positioned between the first fin area 612 and a second fin area 615. In another embodiment, the Dacron® polymer mesh is attached only to either first fin area 612 or the second fin area 615. In other embodiments, the fin 120 is similarly reinforced with a layer of any polymeric material.

FIGS. 22(e) and 22(f) illustrate an alternative embodiment of the lead electrode assembly 100. This embodiment is substantially similar to the embodiment illustrated in FIGS. 22(a)-22(d). The backing layer 610 is substantially similar to the backing layer 610 illustrated in FIG. 22(a). The backing layer 610 in this embodiment, however, is cut along line 617. The fin 120 of this embodiment comprises a proximal edge 129. The proximal edge 129 of the fin 120 is slope-shaped. The sloped shape can reduce the resistance offered by the tissue of the patient as it slides against the fin 120 during the insertion of the lead electrode assembly 100 into the patient.

FIGS. 23(a) and 23(b) illustrate a property of the embodiment of the lead electrode assembly 100 illustrated in FIGS. 22(e) and 22(f). The backing layer 610 is flexible, such that the substantially planar fin 120 formed therefrom is flexible and able to fold. Because the ability of the fin 120

to fold effectively reduces its appendage height, it may make the fin more comfortable to the patient after it is implanted.

FIG. 23(a) shows fin 120 in an upright condition. When pressure is applied perpendicular to the first surface 131 of backing layer in the first fin area 612, along line 677 for example, the fin 120 folds as shown in FIG. 23(b). When the fin 120 folds, its appendage height,  $H_{\text{Appendage}}$ , is reduced. This can be seen by a comparison between FIG. 23(a) and FIG. 23(b).

The backing layer 610 in this embodiment is formed of a polymeric material. In an alternative embodiment, the backing layer 610 is formed of any bio-compatible, flexible polymeric material.

FIGS. 24(a)-24(c) illustrate an alternative embodiment of the lead electrode assembly 100. This embodiment is substantially similar to the embodiment illustrated in FIGS. 22(a)-22(d).

As shown in FIG. 24(a), however, the material from the first fin area 612 and the second fin area 615 of the backing layer 610 is not fastened together with stitching 660 in this embodiment. The resulting appendage 118 is formed in the shape of a tube.

In alternate embodiments, the backing layer 610 is coupled to the electrode 107 such that the material from the first fin area 612 and the second fin area 615 of the backing layer 610

does not touch except at the dividing line 617 between the first fin area 612 and the second fin area 615. The separation between the first fin area 612 and the second fin area 615 of the backing layer 610 can allow the appendage 118 of this embodiment to be highly flexible. This flexibility can reduce the resistance offered by the tissue of the patient as it slides against the appendage 118 during the insertion of the lead electrode assembly 100 into the patient.

FIG. 24(b) illustrates a side plan view of the embodiment illustrated in FIG. 24(a). The appendage 118 of this embodiment comprises a proximal edge 129. The proximal edge 129 of the appendage 118 is slope-shaped. The sloped shape can reduce the resistance offered by the tissue of the patient as it slides against the appendage 118 during the insertion of the lead electrode assembly 100 into the patient.

In alternate embodiments, the proximal edge 129 of the tube formed by the appendage 118 is closed. In one embodiment, the proximal edge 129 of the appendage 118 is closed by a cap (not shown). In another embodiment, the proximal edge 129 of the appendage 118 is closed with stitching placed between the first fin area 612 and the second fin area 615 only at the proximal edge 129 of the appendage 118. In another embodiment, the proximal edge 129 of the appendage 118 is closed by any other means known in the art for this purpose.

FIG. 24(b) illustrates a top plan view of the embodiment illustrated in FIGS. 24(a)-24(b).

FIGS. 25(a)-25(d) illustrate an alternative embodiment of the lead electrode assembly 100. This embodiment is substantially similar to the embodiment illustrated in FIGS. 15(a)-15(b). The backing layer 130 of this embodiment, however, lacks an integrated fin 120.

FIG. 25(a) illustrates a front plan view of the lead electrode assembly. The fin 120 in this embodiment comprises a fin head 700 and flexible joining material 702.

The fin head 700 comprises a rectangular sheet having a first face 705, a second face 706, a first end 710 and a second end 712. The fin head 700 further comprises a height measured along the first face 705 between the first end 710 and the second end 712 and a length measured perpendicular to its height.

The fin head 700 is made of rigid silicone, which has a high durometer. In alternate embodiments, the fin head 700 is composed of any rigid bio-compatible material, such as a rigid bio-compatible polymeric material.

The flexible joining material 702 comprises a rectangular sheet having a first face 720, a second face 721, a first end 718 and a second end 719. The flexible joining material 702 further comprises a height measured along the first face between

the first end 718 and the second end 719. The flexible joining material 702 also comprises a length measured perpendicular to its height. The length of the flexible joining material 702 is the same as the length of fin head 700.

5 The second end 712 of the second face 706 of the fin head 700 is attached to the first end 718 of the first face 720 of the flexible joining material 702. The fin head 700 is attached to the flexible joining material 702 with stitching 725. The second end 719 of the first face 720 of the flexible joining material 702 is attached to the first surface 131 of the backing material 130. The flexible joining material 702 is attached to the backing material 130 with stitching 730.

10 The flexible joining material 702 is made of flexible silicone. It will be recognized by one skilled in the art, however, that the flexible joining material 702 may be made from many other flexible materials, such as a flexible polymeric material.

15 FIG. 25(b) illustrates a property of the fin 120. When pressure is applied perpendicular to the first surface 705 of the fin head 205, the fin 120 folds as shown. When the fin 120 folds, its appendage height,  $H_{\text{Appendage}}$ , is reduced. This can be seen by a comparison between FIG. 25(a), which shows the fin 120 in an upright position and FIG. 25(b) which shows the fin 120 in a folded position.

FIG. 25(c) illustrates a top planar view of the lead electrode assembly 100 of the embodiment illustrated in FIGS. 25(a) and 25(b). Neither the corners of the electrode 107 nor the corners 735 of the backing layer 130 of this embodiment are rounded. In an alternate embodiment, both the corners of the electrode 107 and the corners 735 of the backing layer 130 of this embodiment are rounded.

FIG. 26 illustrates an alternative embodiment of the lead electrode assembly 100. This embodiment is substantially similar to the embodiment illustrated in FIGS. 25(a)-25(d). The backing layer 130 of this embodiment, however, lacks a fin head 700 and flexible joining material 702.

Moreover, the appendage 118 in this embodiment comprises a tube 740 having an interior 755, an exterior 756, a proximal end 757 and a distal end 758. The tube comprises a sheet of material 750. The sheet of material 750 is substantially rectangular having a first pair of sides 751, a second pair of sides 752, a first surface 753 and a second surface 754.

The sheet of material 750 is folded so that its first pair of sides 751 abut each other. The folded sheet of material 750 forms a tube 740. The first surface 753 of the sheet of material 750 faces the interior 755 of the tube 740. The second surface 754 of the sheet of material 750 faces the exterior of the tube 756. In folding the sheet of material 750 so that the



first pair of sides 751 abut each other, the second pair of sides 752 of the sheet of material 750 are folded in a circular shape to form the proximal end 757 and distal end 758 of the tube 740. This results in the tube 740 having a cylindrical shape. The diameter of the circular proximal end 757 and distal end 758 of the tube 756 is approximately 5 mm. In alternate embodiments, the diameter range between approximately 1 mm and approximately 10 mm. The length of the tube 756 as measured between the proximal end 757 and distal end 758 of the tube 756 is approximately 1 cm. In alternate embodiments, length of the tube 756 ranges between approximately 2 mm and approximately 6 cm. In one embodiment, the tube 756 is substantially as long as the electrode 107.

The second surface 754 of the sheet of material 750 is attached to the first surface 131 of the backing layer 130. The first pair of sides 751 of the sheet of material 750 are attached to the backing layer 130 with stitching 760.

In alternate embodiments, the proximal end 757 of the tube 740 is closed. In one embodiment, the proximal end 757 of the tube 740 is closed by a cap (not shown). In another embodiment, the proximal end 757 of the tube 740 is closed by holding one of the second pair of sides 752 of the sheet of material 750 closed with stitching. In another embodiment, the proximal end 757 of

the tube 740 is closed by any other means known in the art for this purpose.

It should be noted that the appendage 118 in some alternative embodiments comprises a tube with a shape other than a cylinder. An example of a tube with a shape other than cylindrical is illustrated below in FIG. 27.

FIG. 27 illustrates an alternative embodiment of the lead electrode assembly 100. This embodiment is substantially similar to the embodiment illustrated in FIG. 26. The tube 740 comprising a sheet of material 750, however, is absent from this embodiment.

Moreover, the appendage 118 of this embodiment comprises a tube 770 having an interior 755 an exterior 756, a proximal end 757 and a distal end 758. The tube comprises a first sheet of material 775, a second sheet of material 776 and a third sheet of material 777. The first sheet of material 775, the second sheet of material 776 and the third sheet of material 777 are all substantially rectangular in shape. Each comprises a first pair of sides 784, a second pair of sides 786, a first surface 788 and a second surface 789. The first pair of sides 784 of each sheet of material are parallel to each other. In another embodiment, the first pair of sides 784 of each sheet of material are non-parallel. The second pair of sides 786 of each sheet of material are parallel to each other. In another

embodiment, the second pair of sides 786 of each sheet of material are non-parallel.

The first pairs of sides 784 of each sheet of material are attached to the first pair of sides 784 of the other sheets of material. In this way the second pair of sides 786 of the first sheet of material 775, the second sheet of material 776 and the third sheet of material 777 form a triangular shaped proximal end 757 and distal end 758 of the tube 770. The sheets of material are attached to each other such that the second surface 789 of each sheet of material faces the interior 755 of the tube 770. The sheets of material are attached to each other with stitching 791.

The height of the tube 770 is approximately 5 mm. In alternate embodiments, the height ranges between approximately 1 mm and approximately 10 mm. The length of the tube 770 as measured between the proximal end 757 and distal end 758 of the tube 770 is approximately 1 cm. In alternate embodiments, length of the tube 770 ranges between approximately 2 mm and approximately 6 cm. In one embodiment, the tube 770 is substantially as long as the electrode 107..

The second sheet of material 776 is attached to the backing layer 130 with stitching 790. The first surface 788 of the second sheet of material 776 is positioned next to the first surface 131 of the backing layer 130.

In alternate embodiments, some or all of the sheets of material are reinforced with a layer of Dacron® polymer mesh. In one embodiment, the Dacron® polymer mesh is attached to the first surface 788 of each sheet of material. In another embodiment, the Dacron® polymer mesh is attached to the second surface 789 of each sheet of material. In another embodiment, the sheets of material are similarly reinforced with a layer of any polymeric material.

In alternate embodiments, the proximal end 757 of the tube 770 is closed. In one embodiment, the proximal end 757 of the tube 770 is closed by a cap. In another embodiment, the proximal end 757 of the tube 770 is closed by holding the sides 786 of the first sheet of material 775, the second sheet of material 776 and the third sheet of material 777 that form the proximal end 757 of the tube 770 together with stitching. In another embodiment, the proximal end 757 of the tube 770 is closed by any other means known in the art for this purpose.

FIGS. 28(a)-28(d) illustrate various possible positions for the appendage 118 relative to the lead 21 of the lead electrode assembly 100. Additionally, up to this point, all embodiments of the electrode 107 illustrated and discussed have had a rectangular shape. These figures illustrate alternative embodiments with electrodes 107 of different shapes.

At this point, it is useful to set out two definitions in order to discuss the possible orientation of appendages 118.

The interface line is defined as the center line of the appendage 118 as traced on the electrode 107. FIG. 28(a) illustrates the interface line 800 of the appendage 118 of a lead electrode assembly 100.

The line of the lead is defined as the line along which the lead 21 of the lead electrode assembly 100 enters the lead fastener 146. The line of the lead 805 of line 21 is shown as it enters the lead fastener 146 (in phantom). As the lead 21 approaches the lead fastener 146, the closest section 807 of the lead 21 forms the line of the lead. When the lead 21 is not bent, the entire lead 21 lies along the line of the lead.

FIG. 28(b) illustrates an embodiment wherein the lead 21 is not bent and the entire lead 21 lies along the line of the lead 805.

The electrode length,  $L_{\text{Electrode}}$ , is the length of the electrode 107 as measured along the interface line 800.

In the embodiments of the lead electrode assembly 100 shown in FIGS. 28(b) and 28(c), the interface line 800 is the same line as the line of the lead 805. In the embodiment shown in FIG. 28(a) the interface line 800 is parallel with the line of the lead 805.

In the embodiment of the lead electrode assembly 100 shown in FIG. 28(d), the interface line 800 intersects the lead fastener 146 (phantom view).

FIGS. 28(e)-28(h) show various additional electrode shapes 5 disposed in various lead electrode assemblies 100. The electrode shapes are not limited, however, to the shapes specifically illustrated.

The electrode 204 depicted in FIG. 28(e) has a "thumbnail" shape. The proximal end 104 of this electrode 107 is generally rounded. As the electrode 107 moves distally along its length, the conductive surface terminates at the distal end 103 of the electrode 107.

An ellipsoidal shaped electrode 107 is depicted in FIG. 28(f). The proximal end 104 of the ellipsoidal shaped electrode 107 is generally rounded. As the ellipsoidal shaped electrode 107 moves distally along its length, the conductive surface terminates in a rounded distal end 103.

A circular shaped electrode 107 is illustrated in FIG. 28(g).

20 A triangular shaped electrode 107 is depicted in FIG. 28(h). Triangular shaped electrodes 107 also incorporate electrodes that are substantially triangular in shape. In particular to FIG. 28(h), the corners of the triangular shaped electrode 107 are rounded.

Several lead electrode assembly manipulation tools 927 have been developed to manipulate the lead electrode assemblies during their surgical implantation.

FIG. 29 illustrates an embodiment of a lead electrode assembly manipulation tool 927. The lead electrode assembly manipulation tool 927 comprises an enhanced hemostat 930 used to manipulate lead electrode assemblies 100 comprising an eyelet during their implantation in patients.

The enhanced hemostat 930 comprises the following components: a hemostat having a first prong 931, a second prong 932, a hinge 939 and an eyelet pin 940. The first prong 931 is attached to the second prong 932 by the hinge 939. The eyelet pin is attached to the second prong 932.

The first prong 931 comprises a first end 933 and a second end 934. The second prong 932 comprises a first end 935 and a second end 936. The first prong and second prong are approximately 75 cm long and curved with a radius of approximately 30 cm. In alternate embodiments, the curvature of the hemostat does not have a radius of approximately 30 cm, but instead approximates the curvature of the thorax of a patient. In one embodiment, the curvature of the hemostat approximates the curvature of the thorax of a patient along a subcutaneous path taken from the anterior axillary line, posteriorly toward the spine.

The first prong 931 is pivotally attached to the second prong 932 by the hinge 939. The hinge is attached to the first prong 931 approximately 10 cm from the first end 933. In this embodiment, the hinge is attached to the second prong 932 approximately 10 cm from the second end 935.

The eyelet pin 940 can be inserted through the eyelet 301 of a fin 120 of the lead electrode assembly 100 such as the lead electrode assembly 100 discussed with reference to FIG. 17(a)-17(g) as a means of capturing the lead electrode assembly 100 prior to its implantation in a patient.

The eyelet pin 940 is a cylindrical member having a first end 941 and a second end 942. In an alternate embodiment, the eyelet pin 940 is a hook-shaped member. The diameter of the cylinder is approximately 2 mm. In alternate embodiments, the diameter of the cylinder ranges from approximately 1 mm to approximately 5 mm. The length of the eyelet pin 940 is approximately 8 mm. In alternate embodiments, the length of the eyelet pin 940 ranges from approximately 4 to approximately 15 mm.

The first end of the eyelet pin 940 is attached to the second prong 932, approximately 8 mm from the second end 936 of the second prong 932. In alternate embodiments, the eyelet pin 940 is attached to the second prong 932 at various lengths from the second end 936 of the second prong 932.



The eyelet pin 940 is attached to the second prong 932 in an orientation perpendicular to the length of the second prong 932. The eyelet pin 940 is attached to the second prong 932 so that it extends away from the second end 934 of the first prong 931.

In this embodiment, all of the components are made of stainless steel. In an alternative embodiment, some or all of the components are composed metals other than stainless steel or are composed of a polymeric material.

We now turn to a discussion of the positions of the components that comprise an entire S-ICD system including the lead electrode assembly 100 when it is implanted in a patient.

FIGS. 30(a) and 30(b) illustrate an embodiment of the S-ICD system implanted in a patient as a means of providing cardioversion/defibrillation energy.

FIG. 30(a) is a perspective view of a patient's ribcage with an implanted S-ICD system. The S-ICD canister 11 is implanted subcutaneously in the anterior thorax outside the ribcage 1031 of the patient, left of the sternum 920 in the area over the fifth rib 1038 and sixth rib 1036. The S-ICD canister 11, however, may alternately be implanted anywhere over the area between the third rib and the twelfth rib. The lead 21 of the lead electrode assembly 100 is physically connected to the S-ICD canister 11 where the transthoracic cardiac pacing energy or

effective cardioversion/defibrillation shock energy (effective energy) is generated. The term "effective energy" as used in this specification can encompass various terms such as field strength, current density and voltage gradient.

5 The lead 21 of the lead electrode assembly 100 travels from the S-ICD canister 11 to the electrode 107, which is implanted subcutaneously in the posterior thorax outside the ribcage 1031 of the patient in the area over the eighth rib 1030 and ninth rib 1034. The electrode 107, may alternately be implanted subcutaneously anywhere in the posterior thorax outside the ribcage 1031 of the patient in the area over the third rib 1030 and the twelfth rib 1034. The bottom surface 115 of the electrode 107 faces the ribcage. The electrode or active surface 15 (phantom view) of the canister 11 also faces the ribcage.

10  
15  
20  
FIG. 30(b) is a cross-sectional side plan view of the patient's rib cage. Here it is seen that the lead 21 travels around the circumference of the thorax, in the subcutaneous layer beneath the fat 1050 between the outside of the ribcage 1031 and the skin 1055 covering the thorax.

We now turn to a discussion of a method by which the lead electrode assembly 100 of the S-ICD system is implanted in a patient using a standard hemostat as well as the enhanced

hemostat described above. FIG. 31 and FIGS. 32(a)-32(d) illustrate aspects of this method.

In operation, as seen in FIG. 31, an incision 905 is made in the patient 900 in the anterior thorax between the patient's third and fifth rib, left of the sternum 920. The incision can alternately be made in any location between the patient's third and twelfth rib. The incision can be made vertically (as shown), horizontally or angulated. In order to minimize scarring, the incision can be made along Langer's lines.

FIG. 32(a) shows a bottom view cross-section of the patient 900, along the line 32(a) shown in FIG. 31. A hemostat 930, with prongs 932 is introduced into the incision 905. The hemostat 930 is inserted with its prongs together without anything gripped between them. The prongs 932 of the hemostat 930 are pushed through the fat 1050 between the skin 1055 of the thorax and the ribcage 1031 to create a subcutaneous path 1090. The prongs 932 of the hemostat 930 can alternately be pushed beneath the fat 1050 that lies between the skin 1055 of the thorax and the ribcage 1031 to create a subcutaneous path 1090 between the fat 1050 and the ribcage 1031.

The hemostat is moved around the ribcage 1031 until the subcutaneous path 1090 reaches within approximately 10 cm of the spine 1035 between the eighth rib 1030 and ninth rib 1034 (this location is best seen in FIG. 30(a)) between the skin 1055 and

the ribcage 1031. The subcutaneous path 1090 can alternately be made to reach any location between the skin 1055 and the ribcage 1031 between the patient's third and twelfth rib. The hemostat 930 is then withdrawn. Alternately, the hemostat 930 can be moved around the ribcage 1031 until the subcutaneous path 1090 terminates at a termination point 1085 at which a line 1084 drawn from the termination point 1085 to the incision 905 would intersect the heart 910.

Next, as shown in FIG. 32(b), the appendage 118 of a lead electrode assembly 100, is squeezed between the tongs 932 of a hemostat 930.

As shown in FIG. 32(c), the lead electrode assembly 100 and hemostat tongs 932 are introduced to the subcutaneous path 1090 and pushed through the subcutaneous path until the lead electrode assembly 100 reaches the termination point 1085 of the path. The appendage 118 of the lead electrode assembly 100 is then released from the tongs 932 of the hemostat 930. The hemostat 930 is then withdrawn from the subcutaneous path 1090.

In an alternative method, the enhanced hemostat 930 seen in FIG. 29 is used to introduce the lead electrode assembly 100 into the subcutaneous path 1090 created as discussed above. After the subcutaneous path 1090 is created, the lead electrode assembly 100 is attached to the enhanced hemostat 930 as shown in FIG. 32(d). Eyelet pin 1108 is inserted through the eyelet

301 in the fin 120 of the lead electrode assembly 100. The enhanced hemostat 930 is then used to introduce the lead electrode assembly 100 into the subcutaneous path 1090, as shown in FIG. 32(c). The lead electrode assembly 100 is then moved  
5 through the subcutaneous path 1090 until the electrode 107 reaches the end of the path 1085. The enhanced hemostat 930 is then moved until the lead electrode assembly 100 is released from the eyelet pin 940. The enhanced hemostat 930 is then withdrawn from the subcutaneous path 1090.

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995  
1000  
1005  
1010  
1015  
1020  
1025  
1030  
1035  
1040  
1045  
1050  
1055  
1060  
1065  
1070  
1075  
1080  
1085  
1090  
1095  
1100  
1105  
1110  
1115  
1120  
1125  
1130  
1135  
1140  
1145  
1150  
1155  
1160  
1165  
1170  
1175  
1180  
1185  
1190  
1195  
1200  
1205  
1210  
1215  
1220  
1225  
1230  
1235  
1240  
1245  
1250  
1255  
1260  
1265  
1270  
1275  
1280  
1285  
1290  
1295  
1300  
1305  
1310  
1315  
1320  
1325  
1330  
1335  
1340  
1345  
1350  
1355  
1360  
1365  
1370  
1375  
1380  
1385  
1390  
1395  
1400  
1405  
1410  
1415  
1420  
1425  
1430  
1435  
1440  
1445  
1450  
1455  
1460  
1465  
1470  
1475  
1480  
1485  
1490  
1495  
1500  
1505  
1510  
1515  
1520  
1525  
1530  
1535  
1540  
1545  
1550  
1555  
1560  
1565  
1570  
1575  
1580  
1585  
1590  
1595  
1600  
1605  
1610  
1615  
1620  
1625  
1630  
1635  
1640  
1645  
1650  
1655  
1660  
1665  
1670  
1675  
1680  
1685  
1690  
1695  
1700  
1705  
1710  
1715  
1720  
1725  
1730  
1735  
1740  
1745  
1750  
1755  
1760  
1765  
1770  
1775  
1780  
1785  
1790  
1795  
1800  
1805  
1810  
1815  
1820  
1825  
1830  
1835  
1840  
1845  
1850  
1855  
1860  
1865  
1870  
1875  
1880  
1885  
1890  
1895  
1900  
1905  
1910  
1915  
1920  
1925  
1930  
1935  
1940  
1945  
1950  
1955  
1960  
1965  
1970  
1975  
1980  
1985  
1990  
1995  
2000  
2005  
2010  
2015  
2020  
2025  
2030  
2035  
2040  
2045  
2050  
2055  
2060  
2065  
2070  
2075  
2080  
2085  
2090  
2095  
2100  
2105  
2110  
2115  
2120  
2125  
2130  
2135  
2140  
2145  
2150  
2155  
2160  
2165  
2170  
2175  
2180  
2185  
2190  
2195  
2200  
2205  
2210  
2215  
2220  
2225  
2230  
2235  
2240  
2245  
2250  
2255  
2260  
2265  
2270  
2275  
2280  
2285  
2290  
2295  
2300  
2305  
2310  
2315  
2320  
2325  
2330  
2335  
2340  
2345  
2350  
2355  
2360  
2365  
2370  
2375  
2380  
2385  
2390  
2395  
2400  
2405  
2410  
2415  
2420  
2425  
2430  
2435  
2440  
2445  
2450  
2455  
2460  
2465  
2470  
2475  
2480  
2485  
2490  
2495  
2500  
2505  
2510  
2515  
2520  
2525  
2530  
2535  
2540  
2545  
2550  
2555  
2560  
2565  
2570  
2575  
2580  
2585  
2590  
2595  
2600  
2605  
2610  
2615  
2620  
2625  
2630  
2635  
2640  
2645  
2650  
2655  
2660  
2665  
2670  
2675  
2680  
2685  
2690  
2695  
2700  
2705  
2710  
2715  
2720  
2725  
2730  
2735  
2740  
2745  
2750  
2755  
2760  
2765  
2770  
2775  
2780  
2785  
2790  
2795  
2800  
2805  
2810  
2815  
2820  
2825  
2830  
2835  
2840  
2845  
2850  
2855  
2860  
2865  
2870  
2875  
2880  
2885  
2890  
2895  
2900  
2905  
2910  
2915  
2920  
2925  
2930  
2935  
2940  
2945  
2950  
2955  
2960  
2965  
2970  
2975  
2980  
2985  
2990  
2995  
3000  
3005  
3010  
3015  
3020  
3025  
3030  
3035  
3040  
3045  
3050  
3055  
3060  
3065  
3070  
3075  
3080  
3085  
3090  
3095  
3100  
3105  
3110  
3115  
3120  
3125  
3130  
3135  
3140  
3145  
3150  
3155  
3160  
3165  
3170  
3175  
3180  
3185  
3190  
3195  
3200  
3205  
3210  
3215  
3220  
3225  
3230  
3235  
3240  
3245  
3250  
3255  
3260  
3265  
3270  
3275  
3280  
3285  
3290  
3295  
3300  
3305  
3310  
3315  
3320  
3325  
3330  
3335  
3340  
3345  
3350  
3355  
3360  
3365  
3370  
3375  
3380  
3385  
3390  
3395  
3400  
3405  
3410  
3415  
3420  
3425  
3430  
3435  
3440  
3445  
3450  
3455  
3460  
3465  
3470  
3475  
3480  
3485  
3490  
3495  
3500  
3505  
3510  
3515  
3520  
3525  
3530  
3535  
3540  
3545  
3550  
3555  
3560  
3565  
3570  
3575  
3580  
3585  
3590  
3595  
3600  
3605  
3610  
3615  
3620  
3625  
3630  
3635  
3640  
3645  
3650  
3655  
3660  
3665  
3670  
3675  
3680  
3685  
3690  
3695  
3700  
3705  
3710  
3715  
3720  
3725  
3730  
3735  
3740  
3745  
3750  
3755  
3760  
3765  
3770  
3775  
3780  
3785  
3790  
3795  
3800  
3805  
3810  
3815  
3820  
3825  
3830  
3835  
3840  
3845  
3850  
3855  
3860  
3865  
3870  
3875  
3880  
3885  
3890  
3895  
3900  
3905  
3910  
3915  
3920  
3925  
3930  
3935  
3940  
3945  
3950  
3955  
3960  
3965  
3970  
3975  
3980  
3985  
3990  
3995  
4000  
4005  
4010  
4015  
4020  
4025  
4030  
4035  
4040  
4045  
4050  
4055  
4060  
4065  
4070  
4075  
4080  
4085  
4090  
4095  
4100  
4105  
4110  
4115  
4120  
4125  
4130  
4135  
4140  
4145  
4150  
4155  
4160  
4165  
4170  
4175  
4180  
4185  
4190  
4195  
4200  
4205  
4210  
4215  
4220  
4225  
4230  
4235  
4240  
4245  
4250  
4255  
4260  
4265  
4270  
4275  
4280  
4285  
4290  
4295  
4300  
4305  
4310  
4315  
4320  
4325  
4330  
4335  
4340  
4345  
4350  
4355  
4360  
4365  
4370  
4375  
4380  
4385  
4390  
4395  
4400  
4405  
4410  
4415  
4420  
4425  
4430  
4435  
4440  
4445  
4450  
4455  
4460  
4465  
4470  
4475  
4480  
4485  
4490  
4495  
4500  
4505  
4510  
4515  
4520  
4525  
4530  
4535  
4540  
4545  
4550  
4555  
4560  
4565  
4570  
4575  
4580  
4585  
4590  
4595  
4600  
4605  
4610  
4615  
4620  
4625  
4630  
4635  
4640  
4645  
4650  
4655  
4660  
4665  
4670  
4675  
4680  
4685  
4690  
4695  
4700  
4705  
4710  
4715  
4720  
4725  
4730  
4735  
4740  
4745  
4750  
4755  
4760  
4765  
4770  
4775  
4780  
4785  
4790  
4795  
4800  
4805  
4810  
4815  
4820  
4825  
4830  
4835  
4840  
4845  
4850  
4855  
4860  
4865  
4870  
4875  
4880  
4885  
4890  
4895  
4900  
4905  
4910  
4915  
4920  
4925  
4930  
4935  
4940  
4945  
4950  
4955  
4960  
4965  
4970  
4975  
4980  
4985  
4990  
4995  
5000  
5005  
5010  
5015  
5020  
5025  
5030  
5035  
5040  
5045  
5050  
5055  
5060  
5065  
5070  
5075  
5080  
5085  
5090  
5095  
5100  
5105  
5110  
5115  
5120  
5125  
5130  
5135  
5140  
5145  
5150  
5155  
5160  
5165  
5170  
5175  
5180  
5185  
5190  
5195  
5200  
5205  
5210  
5215  
5220  
5225  
5230  
5235  
5240  
5245  
5250  
5255  
5260  
5265  
5270  
5275  
5280  
5285  
5290  
5295  
5300  
5305  
5310  
5315  
5320  
5325  
5330  
5335  
5340  
5345  
5350  
5355  
5360  
5365  
5370  
5375  
5380  
5385  
5390  
5395  
5400  
5405  
5410  
5415  
5420  
5425  
5430  
5435  
5440  
5445  
5450  
5455  
5460  
5465  
5470  
5475  
5480  
5485  
5490  
5495  
5500  
5505  
5510  
5515  
5520  
5525  
5530  
5535  
5540  
5545  
5550  
5555  
5560  
5565  
5570  
5575  
5580  
5585  
5590  
5595  
5600  
5605  
5610  
5615  
5620  
5625  
5630  
5635  
5640  
5645  
5650  
5655  
5660  
5665  
5670  
5675  
5680  
5685  
5690  
5695  
5700  
5705  
5710  
5715  
5720  
5725  
5730  
5735  
5740  
5745  
5750  
5755  
5760  
5765  
5770  
5775  
5780  
5785  
5790  
5795  
5800  
5805  
5810  
5815  
5820  
5825  
5830  
5835  
5840  
5845  
5850  
5855  
5860  
5865  
5870  
5875  
5880  
5885  
5890  
5895  
5900  
5905  
5910  
5915  
5920  
5925  
5930  
5935  
5940  
5945  
5950  
5955  
5960  
5965  
5970  
5975  
5980  
5985  
5990  
5995  
6000  
6005  
6010  
6015  
6020  
6025  
6030  
6035  
6040  
6045  
6050  
6055  
6060  
6065  
6070  
6075  
6080  
6085  
6090  
6095  
6100  
6105  
6110  
6115  
6120  
6125  
6130  
6135  
6140  
6145  
6150  
6155  
6160  
6165  
6170  
6175  
6180  
6185  
6190  
6195  
6200  
6205  
6210  
6215  
6220  
6225  
6230  
6235  
6240  
6245  
6250  
6255  
6260  
6265  
6270  
6275  
6280  
6285  
6290  
6295  
6300  
6305  
6310  
6315  
6320  
6325  
6330  
6335  
6340  
6345  
6350  
6355  
6360  
6365  
6370  
6375  
6380  
6385  
6390  
6395  
6400  
6405  
6410  
6415  
6420  
6425  
6430  
6435  
6440  
6445  
6450  
6455  
6460  
6465  
6470  
6475  
6480  
6485  
6490  
6495  
6500  
6505  
6510  
6515  
6520  
6525  
6530  
6535  
6540  
6545  
6550  
6555  
6560  
6565  
6570  
6575  
6580  
6585  
6590  
6595  
6600  
6605  
6610  
6615  
6620  
6625  
6630  
6635  
6640  
6645  
6650  
6655  
6660  
6665  
6670  
6675  
6680  
6685  
6690  
6695  
6700  
6705  
6710  
6715  
6720  
6725  
6730  
6735  
6740  
6745  
6750  
6755  
6760  
6765  
6770  
6775  
6780  
6785  
6790  
6795  
6800  
6805  
6810  
6815  
6820  
6825  
6830  
6835  
6840  
6845  
6850  
6855  
6860  
6865  
6870  
6875  
6880  
6885  
6890  
6895  
6900  
6905  
6910  
6915  
6920  
6925  
6930  
6935  
6940  
6945  
6950  
6955  
6960  
6965  
6970  
6975  
6980  
6985  
6990  
6995  
7000  
7005  
7010  
7015  
7020  
7025  
7030  
7035  
7040  
7045  
7050  
7055  
7060  
7065  
7070  
7075  
7080  
7085  
7090  
7095  
7100  
7105  
7110  
7115  
7120  
7125  
7130  
7135  
7140  
7145  
7150  
7155  
7160  
7165  
7170  
7175  
7180  
7185  
7190  
7195  
7200  
7205  
7210  
7215  
7220  
7225  
7230  
7235  
7240  
7245  
7250  
7255  
7260  
7265  
7270  
7275  
7280  
7285  
7290  
7295  
7300  
7305  
7310  
7315  
7320  
7325  
7330  
7335  
7340  
7345  
7350  
7355  
7360  
7365  
7370  
7375  
7380  
7385  
7390  
7395  
7400  
7405  
7410  
7415  
7420  
7425  
7430  
7435  
7440  
7445  
7450  
7455  
7460  
7465  
7470  
7475  
7480  
7485  
7490  
7495  
7500  
7505  
7510  
7515  
7520  
7525  
7530  
7535  
7540  
7545  
7550  
7555  
7560  
7565  
7570  
7575  
7580  
7585  
7590  
7595  
7600  
7605  
7610  
7615  
7620  
7625  
7630  
7635  
7640  
7645  
7650  
7655  
7660  
7665  
7670  
7675  
7680  
7685  
7690  
7695  
7700  
7705  
7710  
7715  
7720  
7725  
7730  
7735  
7740  
7745  
7750  
7755  
7760  
7765  
7770  
7775  
7780  
7785  
7790  
7795  
7800  
7805  
7810  
7815  
7820  
7825  
7830  
7835  
7840  
7845  
7850  
7855  
7860  
7865  
7870  
7875  
7880  
7885  
7890  
7895  
7900  
7905  
7910  
7915  
7920  
7925  
7930  
7935  
7940  
7945  
7950  
7955  
7960  
7965  
7970  
7975  
7980  
7985  
7990  
7995  
8000  
8005  
8010  
8015  
8020  
8025  
8030  
8035  
8040  
8045  
8050  
8055  
8060  
8065  
8070  
8075  
8080  
8085  
8090  
8095  
8100  
8105  
8110  
8115  
8120  
8125  
8130  
8135  
8140  
8145  
8150  
8155  
8160  
8165  
8170  
8175  
8180  
8185  
8190  
8195  
8200  
8205  
8210  
8215  
8220  
8225  
8230  
8235  
8240  
8245  
8250  
8255  
8260  
8265  
8270  
8275  
8280  
8285  
8290  
8295  
8300  
8305  
8310  
8315  
8320  
8325  
8330  
8335  
8340  
8345  
8350  
8355  
8360  
8365  
8370  
8375  
8380  
8385  
8390  
8395  
8400  
8405  
8410  
8415  
8420  
8425  
8430  
8435  
8440  
8445  
8450  
8455  
8460  
8465  
8470  
8475  
8480  
8485  
8490  
8495  
8500  
8505  
8510  
8515  
8520  
8525  
8530  
8535  
8540  
8545  
8550  
8555  
8560  
8565  
8570  
8575  
8580  
8585  
8590  
8595  
8600  
8605  
8610  
8615  
8620  
8625  
8630  
8635  
8640  
8645  
8650  
8655  
8660  
8665  
8670  
8675  
8680  
8685  
8690  
8695  
8700  
8705  
8710  
8715  
8720  
8725  
8730  
8735  
8740  
8745  
8750  
8755  
8760  
8765  
8770  
8775  
8780  
8785  
8790  
8795  
8800  
8805  
8810  
8815  
8820  
8825  
8830  
8835  
8840  
8845  
8850  
8855  
8860  
8865  
8870  
8875  
8880  
8885  
8890  
8895  
8900  
8905  
8910  
8915  
8920  
8925  
8930  
8935  
8940  
8945  
8950  
8955  
8960  
8965  
8970  
8975  
8980  
8985  
8990  
8995  
9000  
9005  
9010  
9015  
9020  
9025  
9030  
9035  
9040  
9045  
9050  
9055  
9060  
9065  
9070  
9075  
9080  
9085  
9090  
9095  
9100  
9105  
9110  
9115  
9120  
9125  
9130  
9135  
9140  
9145  
9150  
9155  
9160  
9165  
9170  
9175  
9180  
9185  
9190  
9195  
9200  
9205  
9210  
9215  
9220  
9225  
9230  
9235  
9240  
9245  
9250  
9255  
9260  
9265  
9270  
9275  
9280  
9285  
9290  
9295  
9300  
9305  
9310  
9315  
9320  
9325  
9330  
9335  
9340  
9345  
9350  
9355  
9360  
9365  
9370  
9375  
9380  
9385  
9390  
9395  
9400  
9405  
9410  
9415  
9420  
9425  
9430  
9435  
9440  
9445  
9450  
9455  
9460  
9465  
9470  
9475  
9480  
9485  
9490  
9495  
9500  
9505  
9510  
9515  
9520  
9525  
9530  
9535  
9540  
9545  
9550  
9555  
9560  
9565  
9570  
9575  
9580  
9585  
9590  
9595  
9600  
9605  
9610  
9615  
9620  
9625  
9630  
9635  
9640  
9645  
9650  
9655  
9660  
9665  
9670  
9675  
9680  
9685  
9690  
9695  
9700  
9705  
9710  
9715  
9720  
9725  
9730  
9735  
9740  
9745  
9750  
9755  
9760  
9765  
9770  
9775  
9780  
9785  
9790  
9795  
9800  
9805  
9810  
9815  
9820  
9825  
9830  
9835  
9840  
9845  
9850  
9855  
9860  
9865  
9870  
9875  
9880  
9885  
9890  
9895  
9900  
9905  
9910  
9915  
9920  
9925  
9930  
9935  
9940  
9945  
9950  
9955  
9960  
9965  
9970  
9975  
9980  
9985  
9990  
9995  
10000  
10005  
10010  
10015  
10020  
10025  
10030  
10035  
10040  
10045  
10050  
10055  
10060  
10065  
10070  
10075  
10080  
10085  
10090  
10095  
10100  
10105  
10110  
10115  
10120  
10125  
10130  
10135  
10140  
10145  
10150  
10155  
10160  
10165  
10170  
10175  
10180  
10185  
10190  
10195  
10200  
10205  
10210  
10215  
10220  
10225  
10230  
10235  
1024

The foundation 1105 comprises a flat, substantially planar member, comprising a first pair of sides 1106 and a second pair of sides 1107. The first pair of sides 1106 of the foundation 1105 are substantially linear and substantially parallel. In an alternate embodiment, the first pair of sides 1106 of the foundation 1105 are neither linear nor parallel. The length of the first pair of sides 1106 of the foundation 1105 is approximately 2 cm. In alternate embodiments, the length of the first pair of sides 1106 of the foundation 1105 ranges from approximately 2 mm to approximately 6 cm. In an alternate embodiment, the first pair of sides 1106 of the foundation 1105 are as long as the electrode 107 (not shown) of the lead electrode assembly 100 (not shown).

The second pair of sides 1107 of the foundation 1105 are substantially linear and substantially parallel. In an alternate embodiment, the second pair of sides 1107 of the foundation 1105 are neither linear nor parallel. The length of the second pair of sides 1107 of the foundation 1105 is approximately 1 cm. In alternate embodiments, the length of the second pair of sides 1107 of the foundation 1105 ranges from approximately 0.5 cm to approximately 3 cm.

The foundation 1105 further comprises a top surface 1120 and a bottom surface 1121. The foundation 1105 has a thickness, measured as the distance between the top surface 1120 and the

bottom surface 1121. The thickness of the foundation 1105 is 2 mm. In alternate embodiments, the thickness of the foundation 1105 ranges between approximately 1 mm and approximately 5 mm.

Turning now to the riser 1110, the riser 1110 comprises a flat, substantially planar protrusion from the top surface 1120 of the foundation 1105 of the rail 1100. The riser comprises a first face 1125, a second face 1126, a top 1127, a bottom 1128, a proximal end 1123 and a distal end 1124. The first face 1125 and second face 1126 are parallel to each other and perpendicular to the top surface 1120 of the foundation 1105. The first face 1125 and a second face 1126 of the riser 1110 are parallel to the first pair of sides 1106 of the foundation 1105. The bottom 1128 of the riser 1110 joins the foundation 1105 in a position centered between the first pair of sides 1106 of the foundation 1105. The proximal end 1123 of the riser 1110 and the distal end 1124 of the riser 1110 are parallel to each other and perpendicular to the top surface 1120 of the foundation 1105. In other embodiments, the proximal end 1123 of the riser 1110 and the distal end 1124 of the riser 1110 are not parallel to each other.

In one embodiment, the proximal end 1123 of the riser 1110 is not perpendicular the top surface 1120 of the foundation 1105. Instead, the proximal end 1123 of the riser 1110 is sloped, so that the proximal end 1123 and the distal end 1124 of

the riser 1110 are closer at the top 1127 of the riser 1110 than at the bottom 1128 of the riser. A slanted proximal end 1123 make the rail 1100 of the lead electrode assembly 100 offer less resistance against the tissues of the patient during insertion  
5 into the patient.

The height of the riser,  $H_{\text{riser}}$ , is measured as the distance between the top surface 1120 of the foundation 1105 to the head 1115, perpendicular to the top surface 1120 of the foundation 1105. The height of the riser is approximately 5 mm. In  
10 alternate embodiments, the height of the riser ranges from approximately 1 mm to approximately 10 mm.

The riser 1110 has a width, measured as the distance between the first face 1125 and the second face 1126. The width of the riser 1110 is 2 mm. In alternate embodiments, the width of the riser 1110 ranges from approximately 1 mm to approximately 6 mm.

Turning now to the head 1115, the head 1115 is a flat, substantially planar member. The head 1115 comprises a first pair of sides 1136, a second pair of sides 1137, a top surface  
20 1116 and a bottom surface 1117 (not shown). The first pair of sides 1136 and the second pair of sides 1137 of the head 1115 are substantially linear and substantially parallel. In an alternate embodiment, the first pair of sides 1136 of the head 1115 are neither linear nor parallel. In an alternate



embodiment, the second pair of sides 1137 of the head 1115 are neither linear nor parallel.

The length of the first pair of sides 1136 of the head 1115 is equal to the length of the first pair of sides 1106 of the foundation 1105. In alternate embodiments, the length of the first pair of sides 1136 of the head 1115 is unequal to the length of the first pair of sides 1106 of the foundation 1105. The length of the second pair of sides 1137 of the head 1115 is approximately 5 mm. In alternate embodiments, the length of the second pair of sides 1137 of the head 1115 ranges from approximately 3 mm to approximately 10 mm.

The bottom surface 1117 of the head 1115 joins the top 1127 of the riser 1110 opposite the foundation 1105 of the rail 1100. The top surface 1116 and the bottom surface 1117 of the head 1115 are parallel to the top surface 1120 of the foundation 1105. In an alternate embodiment, the top surface 1116 and the bottom surface 1117 of the head 1115 are not parallel to the top surface 1120 of the foundation 1105.

The head 1115 has a thickness, measured as the distance between the top surface 1116 and the bottom surface 1117 of the head 1115. The thickness of the head 1115 is approximately 2 mm. In alternate embodiments, the thickness of the head ranges between approximately 2 mm and approximately 10 mm.

The foundation 1105, the head 1115 and the riser 1110 are made of stainless steel. In alternate embodiments, some or all of the sections of the rail 1100 are made of metals other than stainless steel. In alternate embodiments, some or all of the sections of the rail 1100 are made of a polymeric material wherein the polymeric material is selected from the group consisting essentially of a polyurethane, a polyamide, a polyetheretherketone (PEEK), a polyether block amide (PEBA), a polytetrafluoroethylene (PTFE), a silicone and mixtures thereof.

The foundation 1105, the head 1115 and the riser 1110 are machined from the same piece of material. In an alternate embodiment, some or all of the sections are formed independently and welded to the others.

Turning in detail to FIG. 33(b), the position of the rail 1100 within the lead electrode assembly 100 will be discussed. The rail 1100 is positioned so that its bottom surface 1121 is adjacent to and covers a region of the first surface 131 of the backing layer 130. The rail is centered between the first side 133 and second side 134 of the backing layer 130. In an alternate embodiment, the rail is not centered between the first side 133 and second side 134 of the backing layer 130.

In an alternate embodiment, there is no backing layer 130 and the rail 1100 is positioned so that its bottom surface 1121 is adjacent to the top surface 110 of the electrode 107.

Turning now to the electrode 107 of this embodiment, the electrode 107 is the same shape and size as the electrode 107 discussed with reference to FIGS. 17(a)-(g). In alternative embodiments, the length of the first pair of sides 108 (not shown) and second pair of sides 109 (not shown) of the electrode 107 range independently between approximately 1 cm and approximately 5 cm.

Turning now to the molded cover 220, the skirt 222 of the molded cover 220 partially covers the bottom surface 115 of the electrode 107 as discussed with reference to FIG. 17(d). The molded cover 220 further substantially covers the first surface 131 of the backing layer 130. The molded cover 220 does not cover the first surface 131 of the backing layer 220 in the region in which the bottom surface 1121 of the rail 1100 is adjacent to the backing layer 130. Instead, the molded cover 220 in this region substantially covers the top surface 1120 of the rail 1100. The molded cover 220 abuts the first face 1125 and second face 1126 of the riser 1110 of the rail 1100.

Turning to FIG. 33(c), the position of the lead 21 and the appendage 118 will now be discussed. The interface line 800 of the appendage 118 and the line of the lead 805 are the same line. In an alternate embodiment, interface line 800 of the appendage 118 and the line of the lead 805 are not the same line. The line of the lead 805 is centered between the first

pair of sides 108 (phantom view) of the electrode 107 (phantom view). In an alternate embodiment, the line of the lead 805 is not centered between the first pair of sides 108 of the electrode 107.

5 FIG. 34 illustrates an alternative embodiment of the lead electrode assembly 100. This embodiment is substantially similar to the embodiment illustrated in FIGS. 33(a)-33(c). In this embodiment, however, the dimensions of the electrode 107 are different from those of the embodiment illustrated in FIGS. 33(a)-33(c).

10 The first pair of sides 108 of the electrode 107 (phantom view) are approximately 2.4 cm in length. The second pair of sides 109 of the electrode 107 are approximately 4 cm in length. In alternative embodiments, the length of the first pair of sides 108 and second pair of sides 109 of the electrode 107 range independently between approximately 1 cm and approximately 5 cm.

20 The interface line 800 of the rail 1100 is parallel to the line of the lead 805. In an alternate embodiment, the interface line 800 of the rail 1110 is not parallel to the line of the lead 805. The interface line 800 of the rail 1100 is centered between the first pair of sides 108 of the electrode 107. In an alternate embodiment, the interface line 800 of the rail 1100 is

not centered between the first pair of sides 108 of the electrode 107.

The line of the lead 805 is not centered between the first pair of sides 108 of the electrode 107. Because the lead 805 is not centered between the first pair of sides 108 of the electrode 107, the lead rail 1110 may be more easily accessed by a lead electrode manipulation tool (not shown). In an alternate embodiment, the line of the lead 805 is centered between the first pair of sides 108 of the electrode 107.

FIG. 35 illustrates a lead electrode assembly manipulation tool 927 useful for manipulating a lead electrode assembly (not shown) having an appendage 118 comprising a rail 1100 during the implantation of the lead electrode assembly 100 in a patient. Examples of such lead electrode assembly 100 embodiments are shown in FIGS. 33(a)-33(c) and 34.

The lead electrode assembly manipulation tool 927 comprises a handle 1142, a rod 1144 and a rail fork 1146. The handle 1142 is connected to the rod 1144. The rail fork 1146 is also connected to the rod 1144.

The rod 1144 is a cylindrical member with a diameter of approximately 4 mm, approximately 25 cm in length, having a proximal end 1147 and a distal end 1148. The rod 1144 is curved with a radius of approximately 20 cm.

The rod is made of steel. In other embodiments, the rod is composed of titanium, a polymeric material or any other material suitable for this purpose.

5 The handle 1142 is a cylindrical member with a diameter sized to fit comfortably in the palm of a surgeon's hand. The rod is connected to the proximal end 1147 of the rod 1144. In an alternate embodiment, the handle 1142 is not cylindrical. In an alternate embodiment, the handle 1142 has ergonomic contours.

10 The handle is made of polyurethane. In an alternate embodiment, the handle is made of any metal, or any polymeric material suitable for this purpose.

15 Turning now to FIG. 35(b), the rail fork 1146 is attached to the distal end 1148 of the rod 1144. The rod further comprises a slot 1162 in its distal end. The rail fork comprises a pair of tines 1151 separated by a gap 1153 and a tine base 1160 having a tang 1161.

20 Each of the pair of tines 1151 has a proximal end 1154 and a distal end 1155. The proximal ends 1154 of the pair of tines 1151 are attached to the tine base 1160. Each of the pair of tines 1151 has a substantially rectangular form with straight inner sides 1156 and straight outer sides 1157. The distal ends 1155 of each of the pair of tines 1151 are rounded. The length of the pair of tines 1151, measured from the distal end 1155 to

the proximal end 1154, is substantially equal to the length of the first pair of sides 1106 of the rail 1100 of the lead electrode assembly 100. In alternate embodiments, the length of the pair of tines 1151 is substantially greater than or less than the length of the first pair of sides 1106 of the rail 1100.

The pair of tines 1151 are separated by a gap 1153 formed by the inner sides 1156 of the pair of tines 1151 and the tine base 1160.

The pair of tines 1151 and the tine base 1160 comprising the rail fork 1146 are punched from a single sheet of steel having a thickness of approximately 3 mm. In other embodiments, the rail fork 1146 is composed of titanium, a polymeric material or any other material suitable for this purpose. In one embodiment, the handle 1142, the rod 1144 and the rail fork 1146 are all made from the same piece of material.

FIG. 35(c) illustrates a side plan view of the lead electrode assembly manipulation tool 927. The rod 1144 further comprises a slot 1162 in its distal end 1148. The tine base 1160 connects the pair of tines 1151 to the distal end 1148 of the rod 1144. The tine base 1160 comprises a tang 1161 (phantom view). The tang 1161 is inserted in the slot 1162 in the rod 1144. The tang 1161 is welded in the slot 1162 of the rod 1144.

We now turn to a description of the use of the lead electrode assembly manipulation tool 927 in the implantation of a lead electrode assembly 100 into a patient.

As discussed with reference to FIG. 31, an incision 905 is made in the patient 900. As discussed with reference to FIG. 32(a), a subcutaneous path 1090 is created in the patient 900 with a hemostat 932.

As shown in FIG. 35(d), the lead electrode assembly 100 is then captured by the lead electrode assembly manipulation tool 927. The rail 1110 of the lead electrode assembly 100 is inserted into the rail fork 1146 of the lead electrode assembly manipulation tool 927. The riser 1110 (phantom view) of the rail is placed into the gap 1153 between the pair of tines 1151 of the rail fork 1146. The pair of tines 1151 fit between the bottom surface 1117 of the head 1115 of the rail 1100 and the molded cover 220. The rail 1100 is slid toward the proximal end 1155 of the pair of tines 1151 until the riser 1110 of the rail 1100 reaches the tine base 1160 of the rail fork 1146. The lead 21 of the lead electrode assembly 100 can then be pulled in toward the handle 1142 of the lead electrode assembly manipulation tool 927 until it is taught. This acts to prevent the rail 1100 of the lead electrode assembly 100 from sliding toward the distal end 1151 of the pair of tines 1151 of the rail fork 1146.



As discussed with reference to FIG. 32(c), the lead electrode assembly manipulation tool 927 may then be used to place the lead electrode assembly 100 into the incision 905 of the patient 900 and used to move the electrode 107 to the termination point 1085 of the subcutaneous path 1090.

The lead electrode assembly 100 is then released from the lead electrode assembly manipulation tool 927. To achieve this, the lead 21 of the lead electrode assembly 100 is released so that the pair of tines 1151 of the rail fork 1146 of the lead electrode assembly manipulation tool 927 can slide relative to the rail 1100 of the lead electrode assembly 100. The lead electrode assembly manipulation tool 927 may then be extracted from the subcutaneous path 1090, leaving the lead electrode assembly 100 behind.

FIGS. 36(a)-36(b) illustrate an alternative embodiment of the lead electrode assembly 100. This embodiment is substantially similar to the embodiments illustrated in FIGS. 17(a)-17(g). The backing layer 130 of this embodiment, however, lacks an integrated fin tab 180. Moreover, the lead electrode assembly 100 of this embodiment further comprises a pocket 1300.

FIG. 36(a) illustrates a cross-sectional side plan view of this embodiment. The pocket 1300 comprises a layer of material 1315 and stitching 360. The pocket further comprises an interior 1305 and an opening 1310. The layer of material 1315

is attached to the molded cover 220 with the stitching 360. The molded cover 220 is, in turn, attached to the electrode 107.

The molded cover 220 comprises an outer surface 1330 and a top surface 1331. The outer surface 1330 of the molded cover 220 is the surface of the molded cover 220 that does not lie adjacent to the backing layer 131 or the electrode 107. The top surface 1331 of the molded cover 220 faces away from, and parallel to the electrode 107.

The layer of material 1315 of the pocket 1300 comprises an inner face 1316 and an outer face 1317. The layer of material 1315 is attached to the top surface 1331 of the molded cover 220 so that the inner face 1316 of the layer of material 1315 faces the top surface 1331 of the molded cover 220. The inner face 1316 of the layer of material 1315 also faces the top surface 110 of the electrode 107.

The layer of material 1315 is made of polyurethane. In other embodiments, the layer of material 1315 is made of any bio-compatible material suitable for this purpose. In other embodiments, the layer of material 1315 is made of any bio-compatible polymeric material.

The stitching 360 fastening the layer of material 1315 to the top surface 1331 of the molded cover 220 is comprised of nylon. In alternate embodiments, the stitching 360 comprises any polymeric material.

FIG. 36(b) illustrates a top plan view of the lead electrode assembly 100 of FIG. 36(a). The top surface 1331 of the molded cover 220 has a first side 1333, a second side 1334, a distal end 1336, a proximal end 1337, a length and a width.

5 The distal end 1336, proximal end 1337, first side 1333 and second side 1334 of the top surface 1331 of the molded cover 220 are positioned substantially over the distal end 137 (phantom view), proximal end 138 (phantom view), first side 133 (not shown) and second side 134 (not shown) of the backing layer 130 (phantom view) respectively.

10 The width of the top surface 1331 of the molded cover 220 is measured as the distance between the first side 1333 and second side 1334 of the back surface. The length of the top surface 1331 of the molded cover is measured as the distance between the distal end 1336 and proximal end 1337 of the molded cover 220.

15 The layer of material 1315 comprises a periphery 1318 and a middle portion 1319. More particularly, the layer of material 1315 comprises a distal end 1320, a proximal end 1321, a first side 1322 and a second side 1323. The periphery 1318 of the layer of material 1315 comprises the distal end 1320, the proximal end 1321, the first side 1322 and the second side 1323 of the layer of material 1315. The middle portion 1319 of the layer of material 1315 comprises the area between the distal end

1320, the proximal end 1321, the first side 1322 and the second side 1323 of the layer of material 1315.

The pocket 1300 formed by the layer of material 1315 further comprises a bounded region 1325 and a center 1326. The bounded region 1325 of the pocket 1300 is attached to the back face 1317 of the molded cover 220. The center 1326 of the pocket 1300 is not attached to the back face 1317 of the molded cover 220. Stitching 360 in the bounded region 1325 is used to attach the layer of material 1315 to the molded cover 220.

In the embodiment under discussion, the bounded region 1325 of the pocket 1300 comprises a portion of the periphery 1318 of the layer of material 1315. The bounded region 1325 of the pocket 1300 comprises the proximal end 1321, the first side 1322 and the second side 1323 of the layer of material 1315. In this embodiment, the bounded region 1325 of the pocket 1300 does not comprise the distal end 1320 of the layer of material 1315. The center 1326 of the pocket 1300 comprises the middle portion 1319 of the layer of material 1315. The bounded region 1325 is curved around the center 1326 of the pocket 1300 in a "U" shape. The bounded region 1325 of the pocket 1300 does not completely enclose the center 1326 of the pocket 1300.

In this embodiment, the bounded region 1325 of the pocket comprises a contiguous portion of the periphery 1318 of the layer of material 1315. In an alternate embodiment, the bounded

region 1325 of the pocket comprises a plurality of segmented portions of the periphery 1318 of the layer of material 1315.

In an alternate embodiment the bounded region 1325 of the pocket 1300 does not comprise any portion of the periphery 1318 of the layer of material 1315. In alternate embodiments, the bounded region 1325 comprises any shape that could be traced on the layer of material 1315 that partially encloses a center 1326. In one embodiment, the bounded region 1325 of the pocket 1300 is a portion of a circle's circumference (not shown) that does not touch the periphery 1318 of the layer of material 1315. The center 1326 is the area inside the circle.

In an alternate embodiment, the pocket 1300 comprises a sheet of molded silicone. The molded silicone is fused to the molded cover 220 in the bounded region 1325.

The opening 1310 of the pocket 1300 comprises the area between the distal end 1320 of the layer of material 1315 and the top surface 1331 of the molded cover 220. The interior 1305 of the pocket 1300 comprises the area between the middle portion 1319 of the layer of material 1315 and the top surface 1331 of the molded cover 220.

The layer of material 1315 is positioned so that its first side 1322 and second side 1323 are positioned over the first side 1333 and second side 1334 of the top surface 1331 of the molded cover 220 respectively. The layer of material 1315 is

positioned so that its proximal end 1321 is positioned over the proximal end 1337 of the top surface 1331 of the molded cover 220.

5 The layer of material 1315 is sized so that its length is shorter than the length of the top surface 1331 of the molded cover 220. In alternate embodiments, the layer of material 1315 is sized so that its length is equal to, or longer than the length of the top surface 1331 of the molded cover 220.

10 The proximal end 1321 of the layer of material 1315 is sized so that its width is substantially equal to the width of the proximal end 1337 of the top surface 1331 of the molded cover 220. The layer of material 1315 is sized so that its width steadily increases toward its distal end 1320.

15 The first side 1318 of the distal end 1320 of the layer of material 1315 is fastened to the first side 1333 of the top surface 1331 of the molded cover 220. The second side 1323 of the distal end 1320 of the layer of material 1315 is fastened to the second side 1334 of the top surface 1331 of the molded cover 220.

20 Since the first end 1322 of the layer of material 1315 is wider than the top surface 1331 of the molded cover 220, the layer of material 1315 separates from the top surface 1331 of the molded cover 220 to form the interior 1305 of the pocket 1300.

In an alternate embodiment, the lead electrode assembly 100 lacks a molded cover 220 and the pocket 1300 is attached directly to the backing layer 130. In another alternate embodiment the lead electrode assembly 100 lacks a molded cover 220 and a backing layer 130 and the pocket 1300 is attached directly to the electrode 107. In a further alternate embodiment, the pocket 1300 is molded as part of the molded cover 220.

FIG. 36(c) illustrates a cross-sectional side plan view of an alternative embodiment of the lead electrode assembly 100. This embodiment is substantially similar to the embodiment illustrated in FIGS. 36(a)-36(b). The backing layer 130 of this embodiment, however, further comprises a fin 120 positioned in the interior 1305 of the pocket 1300. The fin 120 of this embodiment is substantially similar to the fin 120 of the embodiment illustrated in FIG. 17(b).

The fin 120 comprises an integrated fin tab 180 formed on the backing layer 130. The molded cover 220 covers the integrated fin tab 180 to form the fin 120. The integrated fin tab 180 has a slope-shaped proximal edge 183. The sloped-shape of the resulting fin 120 permits the fin 120 to fit deeply into the interior 1305 of the pocket 1300. The hood can act to reduce the resistance presented by the tissues of the patient against the fin 120 and any tool used to grasp the fin 120

during insertion of the lead electrode assembly 100. Such a hood can be placed over any fin discussed in the specification to perform this function or any other function.

In alternate embodiments, appendages other than a fin are positioned between the pocket 1300 and the electrode 107, in the interior 1305 of the pocket 1300. In one embodiment, a loop such as that discussed with reference to FIGS. 21(a)-21(c) is positioned in the interior 1305 of the pocket 1300. In another embodiment, a tube such as that discussed with reference to FIG. 26 is positioned in the interior 1305 of the pocket 1300.

FIG. 37(a) and 37(b) illustrates an alternate embodiment of the lead electrode assembly 100. This embodiment is substantially similar to the embodiment illustrated in FIGS. 36(a)-36(b).

FIG. 37(a) illustrates a bottom plan view of the lead electrode assembly 100 of this embodiment. In this embodiment, the electrode 107 is thumbnail shaped.

FIG. 37(b) illustrates a top plan view of the lead electrode assembly 100 of this embodiment. The top surface 1331 of the molded cover 220 is shaped to accommodate the thumbnail shaped electrode 107.

Like the embodiment discussed with reference to FIGS. 36(a) and 36(b), the pocket 1300 comprises a layer of material 1315. In this embodiment, however, the layer of material 1315 has a



roughly triangular shape. The layer of material 1315 comprises a periphery 1318 and a middle portion 1319. More particularly, the layer of material comprises a first side 1340, a second side 1341 and a third side 1342 of the layer of material 1315. The periphery 1318 of the layer of material comprises the first side 1340, the second side 1341 and the third side 1342 of the layer of material 1315. The middle portion 1319 of the layer of material 1315 comprises the area between the first side 1340, the second side 1341 and the third side 1342 of the layer of material 1315.

In this embodiment, the bounded region 1325 of the pocket 1300 comprises a portion of the periphery 1318 of the layer of material 1315. The bounded region 1325 of the pocket 1300 comprises the first side 1340 and the second side 1341 of the layer of material 1315. The center 1326 of the pocket 1300 comprises the middle portion 1319 of the layer of material 1315. The opening 1310 of the pocket 1300 comprises the third side 1342 of the layer of material 1315 and the top surface 1331 of the molded cover 220. The bounded region 1325 of the pocket 1300 is curved around the center 1326 of the pocket 1300. The bounded region 1325 of the pocket 1300 does not completely enclose the center 1326.

In this embodiment, the bounded region 1325 of the pocket comprises a contiguous portion of the periphery 1318 of the

layer of material 1315. In an alternate embodiment, the bounded region 1325 of the pocket comprises a plurality of segmented portions of the periphery 1318 of the layer of material 1315.

In an alternate embodiment the bounded region 1325 of the pocket 1300 does not comprise any portion of the periphery 1318 of the layer of material 1315.

FIG. 38(a)-38(c) illustrates a lead electrode assembly manipulation tool 927. The lead electrode assembly manipulation tool 927 illustrated is useful for manipulating a lead electrode assembly 100 having a pocket 1300 during the implantation of the lead electrode assembly 100 in a patient. Examples of such a lead electrode assembly 100 embodiments are shown in FIGS. 36(a), 36(b), 37(a) and 37(b).

FIG. 38(a) is a top view of the lead electrode assembly manipulation tool 927 of this embodiment. The lead electrode assembly manipulation tool 927 comprises a handle 1142 (not shown), a rod 1144 and a paddle 1350.

The rod 1144 and handle 1142 are substantially similar to the rod 1144 and handle 1142 of the lead electrode assembly manipulation tool 927 illustrated in FIGS. 35(a)-35(d). The handle 1142 is connected to the rod 1144.

The paddle 1350 is attached to the distal end 1148 of the rod 1144. The paddle 1350 comprises a disk 1351 and a tang 1161 (phantom view).

FIG. 38(b) is a side view of the lead electrode assembly manipulation tool 927 of this embodiment. The tang 1161 is inserted in the slot 1162 in the rod 1144. The tang 1161 is welded into the slot 1162 of the rod 1144.

5 The disk 1351 and the tang 1161 are punched from a single sheet of steel having a thickness of approximately 3 mm. In other embodiments, the disk 1351 and tang 1161 are composed of titanium, a polymeric material or any other material suitable for this purpose. In one embodiment, the handle 1142, the rod 1144 and the paddle 1350 are all made from the same piece of material.

We now turn to FIG. 38(c) for a description of the use of the lead electrode assembly manipulation tool 927 in the implantation of a lead electrode assembly 100 into a patient.

As discussed with reference to FIG. 31, an incision 905 is made in the patient 900. As discussed with reference to FIG. 32(a), a subcutaneous path 1090 is created in the patient 900 with a hemostat 932.

20 The lead electrode assembly 100 is then captured by the lead electrode assembly manipulation tool 927. The paddle 1350 of the lead electrode assembly manipulation tool 927 is inserted into the pocket 1300 of the lead electrode assembly 100. The paddle 1350 is slid into the interior 1305 of the pocket via the opening 1310 of the pocket until it can go no further. At this

point, the paddle 1350 touches the inner surface 1316 of the proximal end 1321 of the layer of material 1315.

The lead 21 of the lead electrode assembly 100 can then be pulled toward the handle 1142 of the lead electrode assembly manipulation tool 927 until it is taught. This acts to prevent the paddle 1350 of the lead electrode assembly manipulation tool 927 from sliding out of the pocket 1300 of the lead electrode assembly 100.

10 The lead electrode assembly manipulation tool 927 may then be used to place the lead electrode assembly 100 into the incision 905 of the patient as seen in FIG. 31. The lead electrode assembly manipulation tool 927 may then be used to move the electrode 107 to the termination point 1085 of the subcutaneous path 1090 created as discussed with reference to FIG. 32(c).

15 The lead electrode assembly 100 is then released from the lead electrode assembly manipulation tool 927. To achieve this, the lead 21 of the lead electrode assembly 100 is released so that the paddle 1350 can slide relative to the pocket 1300 of the lead electrode assembly 100. The lead electrode assembly manipulation tool 927 may then be extracted from the subcutaneous path 1090 leaving the lead electrode assembly 100 behind.

Alternately, a curved hemostat, such as the hemostat 930 discussed with reference to FIG. 32(b) could be inserted in the pocket 1300 of the lead electrode assembly 100. The hemostat could then be used to move the electrode 107 to the termination point 1085 of the subcutaneous path 1090 as discussed above.

Alternately, a curved hemostat, such as the hemostat 930 discussed with reference to FIG. 32(b) could be used to grip the pocket 1300 of the lead electrode assembly 100, and used to move the electrode 107 to the termination point 1085 of the subcutaneous path 1090 as discussed above.

FIGS. 39(a)-39(b) illustrate an alternative embodiment of the lead electrode assembly 100. This embodiment is substantially similar to the embodiment illustrated in FIGS. 38(a)-38(c). The backing layer 130 of this embodiment, however, lacks a pocket 1300. Moreover, the lead electrode assembly 100 of this embodiment further comprises a first channel guide 1401 and a second channel guide 1402.

FIG 39(a) illustrates a cross-sectional rear plan view of the lead electrode assembly 100 of this embodiment. The first channel guide 1401 and a second channel guide 1402 each have an interior 1403 and an opening 1404.

The first channel guide 1401 and the second channel guide 1402 each comprise a strip of material 1406 attached to the molded cover 220.

The strip of material 1406 comprising the first channel guide 1401 is substantially rectangular in shape. The strip of material 1406 comprises a first side 1410 and a second side 1412. The first side 1410 and the second side 1412 of the strip of material 1406 are parallel to each other. In another embodiment, the first side 1410 of the strip of material 1406 is not parallel to the second side 1412.

The strip of material 1406 further comprises an inner surface 1417 and an outer surface 1416. The strip of material is positioned so that the inner surface 1417 of the first side 1410 faces the outer surface 1330 of the molded cover 220. The first side 1410 of the strip of material is attached to the first side 1333 of the top surface 1331 of the molded cover 220. The second side 1412 of the strip of material 1406 is attached to the skirt 222 of the molded cover 220.

The interior 1403 of the first channel guide is formed between the inner face 1417 of the strip of material 1406 and the outer surface 1330 of the molded cover 220.

The second channel guide is formed in substantially the same way on the second side 1334 of the molded cover 220.

FIG. 39(b) illustrates a top plan view of the lead electrode assembly of the embodiment of FIG. 39(a). The strip of material 1406 comprising the first channel guide 1401 is substantially rectangular in shape having a distal end 1413 and

a proximal end 1414. The distal end 1413 and the proximal end 1414 of the strip of material 1406 are parallel to each other. In another embodiment, the distal end 1413 of the strip of material 1406 is not parallel to the proximal end 1414 of the strip of material 1406.

The opening 1404 of the first channel guide 1401 is formed by the distal end 1413 of the strip of material 1406 and the outer surface 1330 of the molded cover 220.

The first side 1410 and the second side 1412 (not shown) of the strip of material 1406 comprising the first channel guide 1401 are positioned so that they lie parallel to the first side 1333 (phantom view) of the molded cover 220.

The second channel guide 1402 is formed and mounted to the lead electrode assembly 100 in substantially the same way as the first channel guide 1401. The first side 1410 and the second side 1412 (not shown) of the strip of material 1406 comprising the second channel guide 1402 are positioned so that they lie parallel to the second side 1333 (phantom view) of the molded cover 220.

The strips of material 1406 are composed of polyurethane. In an alternate embodiment, the strips of material 1406 are composed of any polymeric material. The strips of material 1406 are fastened to the molded cover 220 with stitching 360.

In an alternate embodiment, the strips of material 1406 are made of molded silicone and attached to the molded cover 220 by fusing them to the molded cover 220. In an alternate embodiment, the first channel guide 1401 and the second channel guide 1402 are formed as part of the molded cover 220.

FIG. 40(a)-40(b) illustrates a lead electrode assembly manipulation tool 927. The lead electrode assembly manipulation tool 927 illustrated is useful for manipulating a lead electrode assembly 100 having a first channel guide 1401 and a second channel guide 1402 during the implantation of the lead electrode assembly 100 in a patient. Examples of such a lead electrode assembly 100 embodiments are shown in FIGS. 39(a)-39(b).

FIG. 40(a) illustrates a top plan view of a lead electrode assembly manipulation tool 927. The lead electrode assembly manipulation tool 927 in this embodiment comprises a handle 1142 (not shown), a rod 1144 and a channel guide fork 1446.

The rod 1144 and handle 1142 are substantially similar to the rod 1144 and handle 1142 of the lead electrode assembly manipulation tool 927 illustrated in FIGS. 35(a)-35(d). The handle 1142 is connected to the rod 1144.

The channel guide fork 1446 is attached to the distal end 1148 of the rod 1144. The channel guide fork 1446 comprises a pair of tines 1451 separated by a gap 1455 and a tine base 1450 having a tang 1161.



The pair of tines 1451 each have a proximal end 1452 and a distal end 1453. The proximal ends 1452 of the pair of tines 1451 are attached to the tine base 1450. The pair of tines 1451 have a substantially cylindrical form. The distal end 1453 of each of the pair of tines 1451 is rounded.

The length of the pair of tines 1451 is substantially equal to the length of the first side 1410 of the strips of material 1406 comprising the first channel guide 1401 and second channel guide 1402. In alternate embodiments, the length of the tines 1451 is substantially greater than or less than the length of the first side 1410 of the strips of material 1406 comprising the first channel guide 1401 and second channel guide 1402.

The tines are separated by a gap 1455 between the proximal ends 1452 of the pair of tines 1451. The pair of tines 1451 are substantially straight and substantially parallel to each other.

The tine base 1450 connects the pair of tines 1451 to the distal end 1148 of the rod 1144. The tine base 1450 comprises a tang 1161 (phantom view). The tang 1161 is inserted in a slot 1162 in the rod 1144. The tang 1161 is welded in the slot 1162 of the rod 1144.

The pair of tines 1451 comprising the channel guide fork 1446 are composed of steel and have a diameter of approximately 3 mm. The tine base 1450 comprising the channel guide fork 1446 is punched from a single strip of steel having a thickness of

approximately 3 mm. The pair of tines 1451 are welded to the tine base 1450.

In other embodiments, the channel guide fork 1446 is composed of metal, a polymeric material, or any other material suitable for this purpose. In one embodiment, the handle 1142, the rod 1144 and the channel guide fork 1446 are all made from the same piece of material.

We now turn to FIG. 40(b) for a description of the use of the lead electrode assembly manipulation tool 927 in the implantation of a lead electrode assembly 100 into a patient.

As discussed with reference to FIG. 31, an incision 905 is made in the patient 900. As discussed with reference to FIG. 32(a), a subcutaneous path 1090 is created in the patient 900 with a hemostat 932.

The lead electrode assembly 100 is then captured by the lead electrode assembly manipulation tool 927. The pair of tines 1451 of the lead electrode assembly manipulation tool 927 is inserted into the openings 1404 in the first channel guide 1401 and second channel guide 1402.

The electrode 107 is placed into the gap 1455 between the tines of the channel guide fork 1446. The tines 1451 fit into the interior 1403 of the first channel guide 1401 and second channel guide 1402. The molded cover is slid toward the proximal end 1452 of the tines until it can go no further. The

lead 21 of the lead electrode assembly 100 can then be pulled in toward the handle 1142 of the lead electrode assembly manipulation tool 927 until it is taught. This acts to prevent the lead electrode assembly 100 from sliding toward the distal 5 end 1453 of the pair of tines 1451 of the channel guide fork 1446.

The lead electrode assembly manipulation tool 927 may then be used to place the lead electrode assembly 100 into the incision 905 of the patient as seen in FIG. 31. The lead electrode assembly manipulation tool 927 may then be used to move the electrode 107 through the termination point 1085 of the subcutaneous path 1090 created as discussed with reference to FIG. 32(c).

The lead electrode assembly 100 is then released from the lead electrode assembly manipulation tool 927. To achieve this, the lead 21 of the lead electrode assembly 100 is released so that the pair of tines 1451 of the channel guide fork 1446 of the lead electrode assembly manipulation tool 927 can slide relative to the first channel guide 1401 and second channel 20 guide 1402 of the lead electrode assembly 100. The lead electrode assembly manipulation tool 927 may then be extracted from the subcutaneous path 1090 leaving the lead electrode assembly 100 behind.

FIG. 41(a) illustrates a subcutaneous implantable cardioverter-defibrillator kit 1201 of the present invention.

The kit comprises a group of items that may be used in implanting a S-ICD system in a patient. The kit 1201 comprises  
5 a group of one or more of the following items: an S-ICD canister 11, a lead electrode assembly 100, a hemostat 1205, a lead electrode assembly manipulation tool 927, a medical adhesive 1210, an anesthetic 1215, a tube of mineral oil 1220 and a tray 1200 for storing these items.

In one embodiment, the S-ICD canister 11 is the S-ICD canister 11 seen in, and discussed with reference to FIG. 1.

The lead electrode assembly 100 is the lead electrode assembly 100 with a rail 1100, and discussed with reference to  
FIGS. 33(b) and 33(c). In alternate embodiments, the lead electrode assembly 100 is any lead electrode assembly 100 including an electrode 107 with an appendage 118; a pocket; or a first and second channel guide for positioning the electrode 107 during implantation.

The hemostat 1205 is a curved hemostat made of steel having  
20 a first end 1240 and a second end 1241. The hemostat 1205 has a length, measured between the first end 1240 and the second end 1241 as shown in FIG. 41(b) by dimension  $L_{\text{Hemostat}}$ . The length of the hemostat 1205,  $L_{\text{Hemostat}}$ , is approximately 75 cm. In an alternate embodiments, the hemostat 1205 is a length other than

75 cm. In an alternate embodiment, the hemostat 1205 is the enhanced hemostat seen in, and discussed with reference to FIG. 31.

5 The lead electrode assembly manipulation tool 927 is the lead electrode assembly manipulation tool 927 with a rail fork 1146. In alternate embodiments, the lead electrode assembly manipulation tool 927 is any lead electrode assembly manipulation tool 927 including a paddle or a channel guide fork.

10 The medical adhesive 1210 comprises a roll of clear, 1-inch wide medical adhesive tape. As will be recognized, the medical adhesive could be a liquid adhesive, or any other adhesive substance.

15 The anesthetic 1215 is a one ounce tube of lidocaine gel. This can be used as a local anesthetic for the introduction of the lead electrode assembly 100 as discussed below. As will be recognized, the anesthetic could be any substance that has a pain-killing effect. Alternatively, one could use an injectable form of anesthetic inserted along the path of the lead.

20 The tube of mineral oil 1220 is a one ounce tube of mineral oil. This can be used for oiling parts of the electrode connector block 17 seen in FIG. 1.

The tray 1200 is a box sized to fit the items of the kit 1201. The tray 1200 is composed of molded plastic. In another

embodiment, the tray 1200 is a cardboard box. One skilled in the art will recognize that the tray 1200 may comprise any container capable of containing the items of the kit. In one embodiment, the tray is formed with recessed partitions 1230 that generally follow the outline of the items of the kit 1201 to be stored in the tray. In one embodiment, the tray 1200 has packaging material 1225 disposed over it, wherein the packing material 1225 provides a sanitary cover for the items of the kit 1201. The packaging material 1225 further acts to contain the items of the kit 1201.

In an alternate embodiment the kit 1201 comprises ten lead electrode assemblies 100 each comprising a lead 21 having a lead length,  $l_{\text{Lead}}$ , different from the others. In one embodiment, the lead lengths range between approximately 5 cm and approximately 52 cm with approximately a 10 cm difference between the lead length of each lead electrode assembly 100.

In an alternative embodiment, the kit 1201 comprises an S-ICD canister 11, a hemostat 1205 and an assortment of lead electrode assemblies 100 each comprising a lead 21 having a lead length,  $l_{\text{Lead}}$ , different from the others.

In one embodiment, the kit 1200 further comprises a tray 1201 and an assortment of lead electrode assemblies 100, each with an electrode 107 curved at a radius  $r$  different from the others.

In another embodiment, the kit 1200 includes components sized for surgery on a patient of a particular size. A kit 1200 for a 10 year old child, for example, includes an S-ICD canister 11 with a length of approximately 10 cm, a lead electrode assembly 100 with a lead length,  $L_{Lead}$  of approximately 12 cm and a radius  $r$  of approximately 10 cm and hemostat 1205 with a hemostat length,  $L_{Hemostat}$ , of approximately 12 cm.

The S-ICD device and method of the present invention may be embodied in other specific forms without departing from the teachings or essential characteristics of the invention. The described embodiments are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than by the foregoing description and all changes which come within the meaning and range of equivalency of the claims are therefore to be embraced therein.